State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division

		API # (assigned by OCD)	
		30-0	045-27303
. Type of Well		5.	Lease Number Fee
GAS		6.	State Oil&Gas Lease
. Name of Operator		7.	Lease Name/Unit Name
BURLINGTON			·
RESOURCES OIL &	GAS COMPANY	0	Culpepper Martin Well No.
Address & Phone No. of Operate	or	8.	#109
PO Box 4289, Farmington, NM		9.	Pool Name or Wildcat
			Basin Fruitland Coal
. Location of Well, Footage, Se			Elevation:
1460'FSL, 1350'FWL, Sec.32, T	-32-N, R-12-W, NMPM, Sa	in Juan County,	NM
Type of Submission	Type of Act	ion	
X Notice of Intent	Abandonment	Change of Pl	ans
	Recompletion	New Construc	
Subsequent Report	Plugging Back	Non-Routine	
	Casing Repair	Water Shut o	ff
Final Abandonment	Altering Casing	Conversion t	o Injection
	X Other - Pump Insta	allation	
It is intended to install procedure and wellbore dia		well according	to the attached
		APON.	·.
	Q	m 40 30	
		14 O 5 8 2 "	
	•.	6000 1990	7/11
		~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	
SIGNATURE SIGNY (ale	Regulatory Admin	nistratorDece	ember 27, 1999
(trc	
This space for State Use)	1		
	<u> </u>	& GAS INSPECTOR, DI	st. #3 DEC 2 9 19
SHOWAL SIGNED BY CHARLIE		K 1487 MENTILITAD DI	

Culpepper Martin #109 PUMPING UNIT INSTALLATION PROCEDURE 12/9/99

Unit K, Section 32, T32N, R12W, San Juan County, New Mexico Aircare Lat. 36 56.34' Aircare Long. 108 7.34'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH/NUBOP.
- 4. PU AT LEAST 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 2240', THERE ARE 69 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 2209').
- 6. PU 3-7/8" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 2264'. PURGE VALVE WILL BE ON BOTTOM W/2-3/8"x10' PUP JOINT(2254'-2264'), 2-3/8"x6' PUP JOINT(2248'-2254'), 2-3/8"x4' PERFORATED SUB(2244'-2248') AND 2-3/8" SN @ 2244'.
- 8. HANG TBG, IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/2"x14' RWAC), 3' SPRAY METAL PLUNGER, THREE - 1-1/4" SINKER BARS, 87 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4',6',8') TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1-1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Preffared: E.J. Giles Office: 326-9584 Home: 325-8164 Pager: 324-2636

Pump Company is Energy Pump & Supply (505)564-2874

Culpepper Martin #109

12/06/99

Basin Fruitland Coal Unit K, Section 32, T32N, R12W, San Juan County, New Mexico

