

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> dry hole	5. LEASE DESIGNATION AND SERIAL NO. MOO-C-1420-4387
2. NAME OF OPERATOR Wintershall Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME UTE MIN. UTE
3. ADDRESS OF OPERATOR 5 Post Oak Park, Suite 800, Houston, TX 77027	7. UNIT AGREEMENT NAME N/A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FSL & 2210' FWL (SESW) BHL SAME AS ABOVE	8. FARM OR LEASE NAME UTE MIN. UTE
14. PERMIT NO.	9. WELL NO. 34-32N-15W NMPM
15. ELEVATIONS (Show whether OF, RT, GR, etc.) 5941' Ungraded Ground	10. FIELD AND POOL, OR WILDCAT WILDCAT Barker Creek
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 34-32N-15W NMPM
	12. COUNTY OR PARISH San Juan
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PERM OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANE

☐
☐
☒
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

☐
☐
☐☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

RECEIVED
SEP 12 1989

PROPOSED PLUG AND ABANDON PROCEDURE
TIH and place cement plugs as follows:

Plug #1

Pump cement plug from 8806-8495' w/ 177 cu ft Cl "B" w/.5% FL19 cmt.

Plug #2

Pump cement plug from 8345-8245' w/ 59 cu ft Cl "B" w/.5% FL19 cmt.

Plug #3

Pump cement plug from 7993-7893' w/ 65 cu ft Cl "B" w/.5% FL19 cmt.

Plug #4

Pump cement plug from 5495-5395' w/ 89 cu ft Cl "B" w/.5% FL19 cmt.

Plug #5

Pump cement plug from 4592-4100' w/ 307 cu ft Cl "B" cmt.

Plug #6

Pump cement plug from 2660-2560' w/ 71 cu ft Cl "B" w/2% CaCl2 cmt.

Plug #7

Pump cement plug from 60 to surface w/ 30 cu ft Cl "B" w/2% CaCl2 cmt.

Rig down cementers and release rig.

18. I hereby certify that the foregoing is true and correct

SIGNED Chasmeine Stone

TITLE Reg & Prod Analyst Supr.

DATE 8/31/89

(This space for Federal or State office use)

APPROVED BY L. Mark Hollis

TITLE ACTING AREA MANAGER

DATE SEP 11 1989

CONDITIONS OF APPROVAL, IF ANY:

None

ORIGINAL COPY

*See Instructions on Reverse Side