

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELL

Do not use this form for proposals to drill or to deepen or reentry to a well. Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
SF 078051 A

6. If Indian, Allottee or Tribe Name
NA

7. If Unit or CA, Agreement Designation
NA

8. Well Name and No.
Storey Fed. CB-34 #1

9. API Well No.
30-045-28891

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Emerald Gas Operating Co.

3. Address and Telephone No.

570 B Turner Dr, "B", Durango CO 81301 (303) 247-1500

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SESW, 1140' FSL & 2078' FWL
"N", Section 34, T32N-R11W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Commence Drilling & drill to topset TD
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Spud well, 5:15 p.m., 12-21-92. Drill 12-1/4" hole to 330' KB. Ran 9-5/8" 36.0 # / ft, J-55, ST & C casing, landed @ 330' KB. Cemented with 225 sx class "B" with 3% CaCl₂. Had good returns, circulate cement to surface. Plug down 5:00 a.m. 12-22-92.
- Drill 8-3/4" hole to topset depth of 2490' KB. Log hole with GR-DIL from TD to base of surface casing. Run 7", 23.0 # / ft, K-55, LT & C casing landed at 2490' KB. Cemented with 200 sx 65-35 Pozmix with 6% gel, 10% salt, 6-1/4 lb/sk Gilsonite and 0.25% TF-4 followed by 200 sx Class "B" with 3% salt, 6-1/4 lb/sk Gilsonite and 0.25% TF-4. Good returns. Circulate cement to surface. Plug down 9:15 p.m. 12-24-92. Rig down. Release rig 12-25-92.
- Well waiting on weather and cavitation rig for drill out and completion of Fruitland coal pay zone.

14. I hereby certify that the foregoing is true and correct

Signed Bruce Boyce

Title Mgr. of Geol. + Devel.

Date 3/2/93

(This space for Federal or State office use)

Approved by _____

Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

Date _____

MAR 1 3 1993