

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(New concept in
reporting on
"water" and
"water" only)

FOR APPROVED
OMB NO. 1004-0137
EXPIRES December 31, 1991

LEASE DESIGNATION AND SERIAL

I-22-IND-2772

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mountain Ute

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL

Ute Com #26

9. API WELL NO.

30-045-29264

10. FIELD AND POOL OR WILDCAT

Barker Dome Desert Crk

11. SEC. T. R. M. OR BLOCK AND SURF OR AREA

Sec 18 T-32 N R-14

12. COUNTY OR PARISH

San Juan

13. STATE

NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1. TYPE OF WELL. OIL ☐ GAS ☒ DEV ☐ OTHER ☐

2. TYPE OF COMPLETION: NEW ☐ VINEY ☐ DEEP ☐ FLOR ☐ DIFF. ☐ OTHER ☐ P&A

3. NAME OF OPERATOR

Meridian Oil Inc

4. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87499 (505) 326-9700

5. LOCATION OF WELL (Report location clearly and in accordance with any state requirements)*

At surface 1270'FNL, 655'FEL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

NSL-3485

RECEIVED
JUL 6 1995
Bureau of Land Management
Durango, Colorado

15. DATE SPUDDED 16. DATE T.D. REACHED 17. DATE COMPL. (Ready to prod.) 18. ELEVATIONS (OF. S&B, ST. CR, ETC.)* 19. ELEV. CASSINERIA

5-4-95

5-27-95

5-30-95

(P&A)

6214 KB

20. TOTAL DEPTH, MD & TV 21. PLUM. BACK T.D. MD & TV 22. IF MULTIPLE COMPL. HOW MANY? 23. INTERVALS DRILLED BY 24. LOTARY TOOLS 25. CABLE TOOLS

8900

0-8900

26. PRODUCING INTERVAL(S). OF THIS COMPLETION—TOP, BOTTOM.

27. WAS DIRECTOR/ SUPERV. NAME

28. TYPE ELECTRIC AND OTHER LOGS RUN

29. WAS WELL CODED

Yes

AIT-LDT-CNT-CR, ML-EPT, DSSI-GPIT, FMI OIL CON. DIV.

29. CARING RECORD (Log of all logs run in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE DIAMETER (IN)	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PUL
16	42.05#	90	24	6.5 yds Redi-mix	
8 5/8	24#	1007	12 1/4	828 cu. ft.	

30. LINER RECORD 31. TUBING RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKED SET

31. PERFORATION RECORD (If perforated, give size and number)

32. ACID. SHOT. FRACTURE CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED

8392-8900 210 sy Class "C" cmt

7932-8382 215 sy Class "C" cmt

5230-5340 112 sy Class "C" cmt

2490-2800 250 sy Class "C" cmt

See back for more squeezes

33. PRODUCTION

DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping—note kind and type of pump) WELL STATUS (Flowing, shut-in, etc.)

DATE OF TEST HOURS TESTED CURED SIZE PROD. FOR TEST PERIOD OIL—GAL. GAS—MCF. WATER—GAL. GAS-OIL RATIO

FLOW. TUBING PERIOD CASING PRODUCTION CALCULATED 24-HOUR RATE OIL—GAL. GAS—MCF. WATER—GAL. OIL GASEOUS-GAL (CO

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *[Signature]*

TITLE Regulatory Affairs

DATE 7/3/95

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

MAILED

4

DIPOLOLOGIC MARKETING

FORMATION		TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
						HEAR. DEPTH	VERT. DEPTH

Greenhorn	2410'	2468'	Highly calc gry sh w/thin lmst.
Graneros	2468'	2540'	Dk gry shale, fossil & carb w/pyrite include.
Dakota	2540'	2743'	Lt to dk gry foss carb sl calc sl silty
			ss w/pyrite incl thin sh bands clay & shale breaks
			interbed grn, brn & red waxy sh & fine to coarse grn ss
Morrison	2743'	3287'	
Todilto LS	3720'	3727'	Dark gray limestone, anhydritic
Entrada SS	3727'	3843'	Orange, fn gr, rdd to sub rdd ss, tight
Chinle	3843'	5342'	Rd to rd brn, soft sh w/occas. thin beds of brn & gry lst
Cutler	5342'	6860'	Siltstone, orange to red, w/sandstones, orange fn grn
Ismay	8062'	8139'	Limestone, fossiliferous in part, shale dk-gray
Desert Creek	8260'	8334'	Limestone, fossiliferous in part, shale dk-gray
Akiah	8334'	8508'	Anhydrite, white to lt gray, dolomite, brown, silty
Barker Creek	8508'	8716'	Limestone, gray fossiliferous, dolomite lt brn-tan