

TEXAKOMA OIL & GAS CORPORATION
LA PLATA 33 NO. 1 (FEE)
FRUITLAND COAL (BASIN)
SAN JUAN COUNTY, NEW MEXICO
795' FSL & 1755' FWL OF SW/4 OF SEC. 33, T 32 N, R 13 W

PROPERTY CODE 17348
OGRID NO. 022521
POOL CODE 71629
API NO. 30 - 045 - 29272
OPERATOR NO. K0652
EL. 5896' (GL); 5901' (KB)
12 1/4" & 7 7/8" - STRAIGHT HOLE

SPUD -- 08/18/95 @ 8:00 A.M. MST
TD -- 08/26/95 @ 4:30 +/- P.M. MST

135' GLM

8-5/8", 24 PPF, J-55, STC, R-3, NEW, API, NORTHSTAR, SURFACE CSG.
CEMENTED W/100 SXS STANDARD + 2 % CaCl₂ + 0.25 PPS FLOCELE MIXED W/5.2
GPS FW @ 15.6 PPG, YIELD OF 1.19 CFS. TOC @ SURFACE. PLUG DOWN @ 3:00 P.M.
MST ON 08/18/95.

RECEIVED
OCT 12 1995
OIL CON. DIV.
DIST. 3

2 3/8", J-55, 4.7 PPF, EUE, 8rd, R-2, NEW, API, TUBING
1 1/2" DOWN HOLE PUMP
72 - 3/4" GRADE C RODS
1 - 6' PONY ROD

(TOTAL PERFORATIONS -- 132)

1844' = EOT ; SN @ 1811'

PERFORATIONS @ 2 SPF, 180 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.

INDUSTRIAL RUBBER 5 1/2" MULTIPLE STAGE PACKER COLLAR.

PERFORATIONS @ 4 SPF, 90 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.

PERFORATIONS @ 2 SPF, 90 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.

5-1/2", 15.5 PPF, J-55, LTC, R-3, NEW, NORTHSTAR, PROD, CASING.
CEMENT: LEAD - 380 SXS HOWCO STANDARD LIGHT + 2% CaCl₂ + 0.25 PPS
FLOCELE MIXED W/ 9.77 GPS FW @ 12.4 PPG, YIELD OF 1.83 CFS; TAIL:
100 SXS STANDARD + 0.6% HALAD-322 MIXED W/ 5.17 GPS FW @ 15.6 PPG,
YIELD OF 1.18 CFS. TOC @ SURFACE. PLUG DOWN @ 2:04 P.M. MST ON 08/27/95.

1887'- 92' (5'), 1894'- 1899' (5')

1977'-80' GLM

2012'- 2023' (11'), 2026'- 2041' (15')
2044'- 48' (4')

2154' GLM
(2156' EL)

toups
10/03/95