maio. -(June 1990)

ONHEDSIATES	
DEPARTMENT OF THE INTERIOR	?
BUREAU OF LAND MANAGEMEN	T

FORM APPROVED Budget Bureau No. 1004-0135				
Eudget Bureau No. 1004-0135				
Expires: March 31, 1993				

5. Lease Designation and Serial No.

N	IR.	Α.	Λ1	Λ	O:	DC.

SUNDRY NOTICES AND REPORTS ON WELLS	
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	
Hen "APPLICATION END DEDLIT " for such proposale (٠.

· - · · · · · · · · · · · · · · · · · ·			The state of the s	L
1. Type of Well Gil Gas Well Gas Gther		Commence of the Commence of th	Bublin	Gall Hamp and No.
2. Name of Operator		Attention:	FEB 1 6 19	Fields A #7B
AMOCO PRODUCTION CO	MPANY	Mary Corley	' 0 19	API Well No. #7B
3. Address and Telephone No.		(0)[]	1 /4/2/00	000.4500555
P.O. BOX 3092 HOUSTON,	TX 77253	(281) 366-	7497 UUC [10.7 3004529679 20. Ebytand Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Descri	otion)		1449T O DUC 19	Blanco Mesaverde
1215' FNL 2195'		34 T 32N R 11W	UNIT C	11. County or Parish, State
				SAN JUAN NEW MEXICO
12. CHECK APPROPR	ATE BOX(s) TO	INDICATE NATURE OF	NOTICE , REF	ORT, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
		Abandonment		Change of Plans
Notice of Intent		Recompletion		New Construction
Subsequent Report		Plugging Back		Non-Routine Fracturing
· ·		Casing Repair Altering Casing	H	Water Shut-Off Conversion to Injection
Final Abandonment Notice		Other Spud and Set Sundry		Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.				

13. Describe Proposed or Completed Operations (Clearly state all pertinent datails, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give

MIRUSU spud a 12.25" surface hole on 12/13/98 at 20:00 hrs. Drilled to 275'. Set 9.625" 36# K-55 surface pipe at 272'. Cemented with 145 sxs CI B cement. Cemented pipe to surface circulating 72 sxs of good cement to surface.

Drill a 8.750" intermediate hole on 12/17/98 at 14:30 hrs. Drilled to 3210'. Set 7.00" 20 & 23# intermediate casing at 3210'. Cemented with 265 sxs CI B lead and 150 sxs CI B tail. Circulate cement to surface . Pressure test to 1200#.

Drill a 6.250" hole to 5810' on 12/20/98. Set 4.50" 10.5# J-55 production liner at 5805' with liner top at 2990'. Cemented with 260 sxs CI B cmt. Circ. colored cmt water with good lift pressure.

Rig released at 16:00 hrs on 12/20/98.

14.1 hereby cartify that the foregoing is true and correct Signed Asy Cosley	Title	Sr. Business Analyst	Date 01-12-1999
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title		.outPHED FOR RECUn.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficticious, or fraudulent statements or representations as to any matter within its jurisdiction. 1999