

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2335' FSL, 1870' FEL, Sec. 35, T-32-N, R-12-W, NMPM, San Juan County

API # (assigned by OCD)

30-045-30487

5. Lease Number

Fee

6. State Oil&Gas Lease #

7. Lease Name/Unit Name

Moore

8. Well No.

#1C

9. Pool Name or Wildcat

Blanco Mesaverde

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - Spud, casing, & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

10-4-01 MIRU. Spud well @ 3:00 pm 10-4-01. Drill to 224'. Circ hole clean. TOOH. TIH w/5 jts 9-5/8" 32.3# H-40 ST&C csg, set @ 219'. Cmdt w/185 sx Class B neat w/3% calcium chloride, 0.25 pps flocele (218 cu ft). Circ 15 bbls cmt to surface. WOC.

10-5-01 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.

10-7-01 Drill to intermediate TD @ 3272'. Circ hole clean. TOOH. TIH w/5 jts 7" 23# N-80 LT&C csg, & 71 jts 7" 20# J-55 ST&C csg, set @ 3266'. Cmdt w/383 sx 50/50 Class G/TXI w/2.5% D-79, 37 pps D49, 0.5 pps D-29, 10 pps D-24, 0.2% D-46, 2% calcium chloride (988 cu ft). Tail w/90 sx 50/50 Class G poz w/2% D-20, 0.25 pps cellophane, 5 pps D24, 2% calcium chloride, 0.1% D-46 (115 cu ft). Circ 60 bbls cmt to surface. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

APD ROW Related

SIGNATURE

*Duffy Call*

Regulatory Supervisor October 9, 2001

TLW

(This space for State Use)

ORIGINAL SIGNED BY CHARLES T. PERLIN

DEPUTY OIL & GAS INSPECTOR, DIST. 5

OCT 11 2001

Approved by

Title

Date