

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT I
P.O. Drawer DD, Artesia, NM 88210

DISTRICT I
1000 Rio Brazons Rd, Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, New Mexico 87505

WELL API NO.

30-045-30696

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL

GAS

WELL ☐

WELL ☒

OTHER

2. Name of Operator

Great Western Drilling Company

3. Address of Operator

c/o Walsh Engineering, 7415 East Main Street, Farmington, NM 87402

4. Well Location

Unit Letter J : 1685' Feet From The South Line and 2185' Feet From The East Line

Section 12

Township

32N Range 12W

NMPM

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6335' GL

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

11. NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG & ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work).
SEE RULE 1103.

8/3/01 Spud well. Set 9-5/8", 36#, J-55 casing at 308' KB. Cement with 197 cu.ft. of Type III cement. Circulated 12 bbls of cement to surface. Installed BOPs and pressure tested to 1500 psi - held OK.

Drilled 8-3/4" hole to 2386' KB and set 7", 20#, J-55 casing at 2386' KB. Cemented with 637 cu.ft. of Premium Lite cement and 113 cu.ft. of Type III cement with additives. Circulated 42 bbls of cement to surface. WOC 12 hrs. Pressure tested casing to 1500 psi - OK.

Drilled a 6-1/4" hole to 5718' and set 4-1/2", 10.5#, J-55 casing at 5714' KB. Cemented with 233 cu.ft. of Premium Lite cement and 381 cu.ft. of Premium Lite cement with additives. Top of cement by CBL is 1020'. Rig released 8/9/01.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Paul C. Thompson

TITLE Agent/Engineer

DATE 11/02/01

TYPE OR PRINT NAME

Paul C. Thompson

TELEPHONE NO. 327-4892

(This space for State

APPROVED BY

ORIGINAL SIGNED BY CHARLIE T. PERKINS

TITLE

PROPERTY OIL & GAS INSPECTOR DIST. 11

DATE

CONDITIONS OF APPROVAL, IF ANY: