NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo]			sverde_	For	mation	<u> </u>	DEATE:		County_	8	in dra	
Init	ial		Annua			Spe	cial	····	Date of	Test_		7
Comp	any p	LAND		LEGAL D	AP.	Lease	eiere!	Case Units	We	ll No	1	
Unit		Sec	20 Twp		Rg	e]	Pı	ırchaser	·			In
Casi	.ng	Wt.	14 I.	0.4. D2	S e	t at	552 914	Perf	49	_To	AASA.	
								Perf.	•			
								GL T				12
								Type W Single-Brad				
Date	of Comp	letion:	7-17-	Я	_Packe	r		Single-Brad Reserv	enhead-G. oir Temp.	G. or	G.O. I	Dual
							VED DAT		•			
Test	ed Throu	gh 🙀	(C)	noke) (inter)				Type Tap	os		
			Flow Dat	a		· · · · · · · · · · · · · · · · · · ·	Tubi	ng Data	Casing I		T	
No.	(Prove (Line	r) (C) (Or	hoke)	Press.	Diff.	Temp.	Pres	s. Temp.	Press.		1	Duration of Flow
SI	Size		ifice) Size	psig	h _w	°F.	psi			[⊃] F.		Hr.
1. 2.			<u> </u>	544			585		LOPS Me	60		3 hrs.
3.												
4. 5.												· · · · · · · · · · · · · · · · · · ·
						FLOW CAI	CULATI	ONS				
No.		icient Hour)	√ h _w p ₁	_	ssure	Flow	Temp.	Gravity Factor Fg	Facto	r	Q-MC	of Flow CFPD 025 psia
1. 2.	12.36			2	D	1,000		0.9298	1.0		7	
3. 4.			ļ									
5.												
			on Ratio drocarbor (1-	is .e ^s)	PRI	cf/bbl.	,	Spec: Spec:	ific Gravi ific Gravi	ty Sepa ty Flow PC_1	ving F	luid
No.	P _w	a) F	Pt FcQ		(F _c Q) ²	(F (1	(cQ) ² (-e ^{-s})	P _w 2	$P_c^2-P_w^2$	Ca	al.	P _w P _c
1. 2.								3%,409	69, 40			
3. 4.												
5.												
COMPA ADDRE AGENT	ESS and TI	PAR AU	MOLGAN P.		How the			.70 12m13	me,			
COMPA	ESSED				······································					7 H	4	
						REM	ARKS		}	" cc	9 /3. N. Co	57

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\scriptsize =}$ Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- $F_t = Flowing$ temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

AZTEC D	VATION CO	FFICE
No. Copies Re		2
Dic	19191(110)	· ·
and the second s	1280	
Description		
1. 5. 10 to 1. 16 to	· 1	;
Dorth Comes		** · · · · · · · · · · · · · · · · · ·
The kinds office		the state of the same of the s
U 18. \$ 18		7
Transporter		Section (Configuration Configuration Configu
5 146		7 2