

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
AUG 29 1996

2. Name of Operator
MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
880' FNL, 1030' FEL, Sec. 33, T-32-N, R-12-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-60079
5. Lease Number
Fee
6. State Oil&Gas Lease #
7. Lease Name/Unit Name
Culpepper Martin SRC
8. Well No.
6
9. Pool Name or Wildcat
Blanco Mesaverde
10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Pay add and restimulation
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

8-20-96 MIRU. ND WH. NU BOP. TOOH w/2 3/8" tbgs. TIH w/5 1/2" csg scraper to 4950'. TOOH.

8-21-96 TIH w/cmt retainer, set @ 4727'. Load hole w/2% KCL wtr. Circ hole clean. Establish injection. Pump 200 sx Class "B" cmt w/0.3% fluid loss, 6.5 pps Gilsonite. Displace 17.5 bbl wtr. Reverse out 0.25 bbl cmt to surface. WOC. PT csg & cmt retainer to 2200 psi/15 min, OK. TIH.

8-22-96 TIH, tag TOC @ 4720'. Drill cmt @ 4720-4727'. Drill cmt retainer @ 4727'. Drill cmt @ 4727-4952'. Blow well & CO to PBTD @ 4981'. PT sqz to 500 psi/15 min, OK. Blow well & CO. Spot 100 gal 15% Hcl @ 4981'. TOOH. Perf Point Lookout w/2 SPF @ 4769, 4779, 4784, 4788, 4799, 4805, 4810, 4816, 4831, 4838, 4842, 4857, 4867, 4872, 4893, 4898, 4919, 4925, 4946, 4962, 4966 w/42 holes total. Frac Point Lookout w/80,000# 20/40 Arizona sd, 15,000# resin coated sd, 1238 bbl 30# x-link gel. CO after frac. TOOH. TIH w/CIBP, set @ 4760'. PT CIBP & csg to 2200 psi/15 min, OK. TOOH.

8-23-96 Blow well & CO to CIBP @ 4760'. Spot 400 gal 15% Hcl. TOOH. Perf Menefee w/2 SPF @ 4567, 4571, 4576, 4581, 4588, 4591, 4621, 4638, 4640, 4660, 4672, 4676, 4691, 4704, 4718, 4724, 4732, 4734' w/36 holes total. Frac Menefee w/80,000# 20/40 Arizona sd, 15,000# resin coated sd, 1175 bbl 30# x-link gel. CO after frac.

8-24-96 Blow well & CO. Drill up CIBP @ 4760'.

8-25-96 Blow well & CO.

8-26-96 Blow well & CO. TOOH. TIH w/159 jts 2 3/8" 4.7# J-55 tbgs, landed @ 4941'. ND BOP. NU WH. RD. Rig released.

SIGNATURE *Regina Brannan* Regulatory Administrator August 27, 1996

(This space for State Use)

Approved by *Johnny Robinson* Title DEPUTY OIL & GAS INSPECTOR, DIST. #3 Date AUG 29 1996