

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Federal <input type="checkbox"/> Fee <input type="checkbox"/>
1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator El Paso Natural Gas Company		7. Unit Agreement Name
3. Address of Operator PO Box 990, Farmington, NM 87401		8. Farm or Lease Name Mansfield
4. Location of Well UNIT LETTER <u>B</u> <u>977</u> FEET FROM THE <u>North</u> LINE AND <u>1700</u> FEET FROM <u>East</u> THE <u>LINE, SECTION 24</u> TOWNSHIP <u>30N</u> RANGE <u>9W</u> N.M.P.M.		9. Well No. 3 (P&A)
10. Field and Pool, or Wildcat Blanco Pictured Cliffs		
15. Elevation (Show whether DF, RT, GR, etc.) 5976'GL		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spotted 100 sks. cement plug on bottom and across perforations.

Perforated four squeeze holes, at 1580' spotted 75 sk. cement plug and squeezed 40 sks. cement out squeeze holes.

Perforated four squeeze holes at 50', squeezed 40 sks. cement out squeeze holes. (left cement at surface inside production casing).

Set Plug & Abandonment marker with 10 sks. cement plug at the surface. Cleaned up location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Original Signed F. H. WOOD TITLE Petroleum Engineer DATE March 15, 1972

APPROVED Original Signed by Amery C. Arnold TITLE Chief Engineer #3 DATE MAR 16 1972

CONDITIONS OF APPROVAL, IF ANY: