

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

Southland Royalty Company

P.O. Drawer 570, Farmington, New Mexico

AT SURFACE: 1045' FSL & 1695' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>
(other)	

[illegible]

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6069' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SOUTHLAND ROYALTY COMPANY proposes to abandon lower Dakota perforations 7155', 7161', 7167', 7173', 7179', 7202', 7208', 7214' (8 holes) by setting Cast Iron Bridge Plug at 7140'. Will spot minimum 50' cement plug on bridge plug when well is permanently abandoned.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Tilden TITLE Dist. Engineer DATE Sept. 22, 1981

(This space for Federal or State office use)

(Orig. Sgd.) RAYMOND W. VINYARD

APPROVED BY _____ TITLE Acting District

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side