

S.W.D AND/OR INJECTION WELL INSPECTION REPORT

API #: 30-045-28653

DATE: 11-1-96 CLASS 1: ☒ CLASS 2: ☐ S.W.D: ☒ INJECTION: ☐

OPERATOR: Coleman O&G Inc.

WELL NAME: Surco Disposal WELL#: 1

LOCATION: UT. LETTER: E SEC: 2 TWN: 29N RGE: 12W

PRESS. LIMIT: 2850 INJ. PRESS: 1350# TBG/CSG ANNULUS PRESS: 1230# *while not injecting

BRADENHEAD PRESS. 0 INTERMEDIATE CSG.PRESS. 111

REQUIRED POSITIVE TBG/CSG ANNULUS PRESS. TO BE MAINTAINED ON WELL AS STIPULATED ON WFX OR S.W.D. ORDER: S.W.D-457 (100#)

TYPE OF PRESSURE LIMITING DEVICE USED: Murphy pressure Kill set @ 2150#

PRESSURE SETTING OF PRESSURE LIMITING DEVICE: 2150#
(PRESSURE SETTING OF PRESSURE LIMITING DEVICE NOT TO EXCEED PRESSURE LIMIT)

REMARKS: S.W.D Last inspected on 9-4-96 by E.C.

Volume totalizer was operational at the time of this inspection

*Tbg/csg annular pressure goes up to 1230# when operator isn't injecting, when well is being injected into, annular pressure drops to 260# - 300# range.

INSPECTOR: [Signature]

WITNESS (IF AVAILABLE): [Signature]