

WELLS WITHIN 1/2 MILE OF PROPOSED INJECTION WELL

<u>Operator</u>	<u>Name</u>	<u>Location</u>	<u>Casing Strings</u>	<u>Setting Depth</u>	<u>Cement Volume</u>	<u>Cement Top</u>	<u>Total Depth</u>	<u>Producing Interval</u>	<u>Producing Formation</u>
Tesoro	SFRR "B" 30	SE/SW, Sec. 5-17N-8W	8 5/8"	137'	100 sx	surface	2736'	P&A	--
Tesoro	SFRR "B" #32	SW/SW, Sec. 5-17N-8W	9 5/8" 5 1/2"	97' 2634'	90 sx 200 sx	surface 1780'	2648'	2634-48'	Dakota
Tesoro	SFRR "B" #33	NW/SW, Sec. 5-17N-8W	8 5/8" 5 1/2"	102' 2636'	100 sx 385 sx	surface 1494'	2652'	1578-82'	U. Hospah
Tesoro	SFRR "B" #34	SW/SW, Sec. 5-17N-8W	8 5/8" 5 1/2"	105' 1632'	90 sx 100 sx	surface 800'	1638'	1588-96'	U. Hospah
Tesoro	SFRR "B" #36	NW/SW, Sec. 5-17N-8W	8 5/8" 5 1/2"	94' 1599'	100 sx 100 sx	surface 1050'	1600'	1564-70'	U. Hospah
Tesoro	SFRR "B" #37	SW/SW, Sec. 5-17N-8W	8 5/8" 5 1/2"	107' 1613'	100 sx 100 sx	surface 1060'	1614'	1574-80'	U. Hospah
Tesoro	Hanson Fed. #23	SE/SE, Sec. 6-17N-8W	8 5/8" 5 1/2"	144' 2724'	100 sx 325 sx	surface 1350'	2725'	2627-31' 2638-50'	Dakota Dakota
Tesoro	Hanson Fed. #25	NW/NW, Sec. 8-17N-8W	8 5/8" 5 1/2"	107' 2741'	75 sx 385 sx	surface 1100'	2750'	2673-78' 2683-93'	Dakota Dakota
Tesoro	Hanson Fed. #26	NW/NW, Sec. 8-17N-8W	8 5/8" 5 1/2"	104' 1653'	100 sx 100 sx	surface 1170'	1654'	1620-26' 1632-35'	U. Hospah U. Hospah
Tesoro	Hanson Fed. #27	SW/SE, Sec. 6-17N-8W	8 5/8" 5 1/2"	103' 1644'	100 sx 100 sx	surface 1130'	1645'	1519-32' 1535-50'	U. Hospah U. Hospah
Tesoro	Hanson Fed. #28	NW/SE, Sec. 6-17N-8W	8 5/8" 5 1/2"	103' 1687'	100 sx 100 sx	surface 1140'	1699'	1576-82'	L. Hospah
Tesoro	Hanson Fed. #30	SE/NW, Sec. 6-17N-8W	8 5/8" 5 1/2"	103' 1643'	100 sx 100 sx	surface 1090'	1643'	1576-84'	L. Hospah
Tesoro	Hanson Fed. #31	SE/NW, Sec. 6-17N-8W	8 5/8" 5 1/2"	85' 1617'	100 sx 100 sx	surface 1070'	1620'	1550-58'	L. Hospah