Form 9-381 b (April 1952)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agen	cy
Jicani	lla-desphe
Allottee	TRIBAL
Lease No	Treat FLO
Contract	In.: Massilla

OTICE OF INTENTION TO DRILL OTICE OF INTENTION TO CHANGE OTICE OF INTENTION TO TEST WAT OTICE OF INTENTION TO REDRILL OTICE OF INTENTION TO SHOOT O OTICE OF INTENTION TO PULL OR OTICE OF INTENTION TO ABANDON	PLANS	EPORT OF WATER SHUT-OFF EPORT OF SHOOTING OR ACIDIZING EPORT OF ALTERING CASING EPORT OF REDRILLING OR THE TANK EPORT OF ABANDONMENT Y WELL HISTORY
(INDICA	TE ABOVE BY CHECK MARK NATURE OF REPORT, N	NOTICE, OR OTHER DATA)
M/4 Sec. 2	cated ft. from S line and	1140 ft. from E line of sec.
(14 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
(Field)	(County or Subdivision)	Nov Menico
	DETAILS OF WORK o objective sands; show sizes, weights, and length ing points, and all other important propos	as of proposed casings; indicate mudding jobs, cement-
	(See Attucked)	(aft)
Note: We have com with Indian	plied with provisions of co Agency prior to staking lo	ontract for checkingNOV 25 105

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Deltad States Smallting Reflecting & Minding Co.

Address Re . Sam 1677

Title Maintage to Manage Title

DETAILS OF WORK

The operator proposes to drill a Pictured Cliff test to a total depth of appreximately 3300' to test for eil and gas.

The following is a brief outline of the proposed work:

Chiestive:

Truitland Pictured Cliff 2860' 3000'

Casing Program:

Serface Casing: 9-5/8", 360 at 150' with sufficient coment

to circulate.

Production Casing: 7", 20# and 23# at 3000' with 150 sacks.

Drill Stem Testing:

All shows of oil or gas will be tested.

Other Proposed Work:

1. An electrical log will be run from shoe of the surface easing to the 7" casing point prior to running 7" easing.

2. A Gamma Ray-Meutron Log will be run from total depth to the surface.

3. Ten foot samples will be caught and sacked from the shoe of surface casing to total depth.