



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. N.M. 0342

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input checked="" type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 24, 1954

Well No. #1 Duff is located 1,980' ft. from N line and 500 ft. from E line of sec. 24

SE 1/4 S 24
(1/4 Sec. and Sec. No.)

24 N 1 W
(Twp.) (Range)

N.M.P.M.
(Meridian)

Wildcat
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7,500 ft. Approximate

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Cement plugs set in following intervals:

8,300'	-	8,453'
7,500'	-	7,600'
7,000'	-	7,250'
6,350'	-	6,500'
5,600'	-	5,750'
5,100'	-	5,200'
4,350'	-	4,500'
2,500'	-	2,600'
2,200'	-	2,300'
1,000'	-	1,150'
600'	-	800'

Cement plug and marker in top of surface csg.
Pits, cellar, reserve backfilled and levelled.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Reading and Bates, Inc. #1 Duff

Address 1502 Philtower Bldg.

Tulsa 3, Oklahoma

By J. W. Bates, Jr.

Title President