

COPY FOR
STATE OF NEW MEXICO
**OIL CONSERVATION
COMMISSION**
SUBMIT IN TRIPLICATE TO
DISTRICT OFFICE

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

Land Office Alamogordo
Lease No. 378769
Unit None Unit
I-Rec. No. 587

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input checked="" type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
JAN 22 1952

OIL CON. COM.
DIST. 3

Farmington, New Mexico, January 18, 1952

Well No. 3 is located 2310 ft. from N line and 330 ft. from W line of sec. 16
1/4 of Section 16 T-11-N 2-3-E 117N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox Alamogordo New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5357 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; well was drilled to a total depth of 3110 feet with the rotary drill in November 12, 1950. As previously reported 7" casing was set at 3100 feet. Hole was cleaned out to total depth with cable tools June, 1950. The well was snubbed June 6, 7, 8 and 9 for 24 hours per day and 3 barrels of water per hour were recovered with a small amount of gas escaping, but not enough to measure. Well was plugged back with cal-seal from 3110 to 3222 feet and was shot June 20 1951, with 240 quarts of 40 from 3192 to 3222 feet with gravel cap from 3192 to 3188 feet and Cal-seal cap from 3188 to 3151 feet. Well was cleaned out to 3220 feet with water rising in hole. Snubbed 3 to 4 barrels of water per hour. Well was snubbed June 21 to June 24 with no change in water and very little gas showing. Well was then determined commercially non-productive.

It is proposed to permanently plug and abandon this well as follows: 1. Plug hole with solid cement from bottom of hole to 3155 feet; 2. Shoot off casing in order to recover maximum footage 7" casing; 3. Place 4 1/2 inch solid cement plug in top of 4 1/2 inch casing; 4. Place a 10 inch solid cement plug in top of hole; 5. Erect 4' pipe marker and restore ground level to original contours as per regulations.

Company STANOLIND OIL AND GAS COMPANY

Address Box 487

Farmington, New Mexico

By L. O. Spivey, Jr.

Title Production Foreman