

STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
DISTRICT NO. 3
Phone 99 P. O. Box 697
AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Santa Fe
Lease No. _____
J1871
Unit _____
Lease Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico, January 15, 1952

Well No. 2 is located 660 ft. from N line and 715 ft. from E line of sec. 11

1/4 of section 11 (Range) (Section) (Municipality)
in San Juan (County or Subdivision) (State of New Mexico)
(Field)

The elevation of the derrick floor above sea level is 5325 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was drilled to a total depth of 3454 feet in 1950. In previously reported 7" casing was landed at 3160 feet. Two hundred ninety-nine feet of 5 1/2" flush joint liner and hanger tools were cemented from 3454 to 3062 feet. In an effort to stimulate any possible production, the open hole interval (3370 to 3425 feet) was shot with 160 quarts of 240. The hole was cleaned out to total depth with no shows of oil or gas.

It is proposed to permanently plug and abandon this well as follows: 1. Plug hole with solid cement from bottom of hole to 3062 feet; 2. Shoot off casing in order to recover maximum footage 7" casing; 3. Place a 15 sack solid cement plug in top of stub to protect water sand logged at approximately 2400 to 2520 feet; 4. Place a 10 sack solid cement plug in top of hole; 5. Erect 4' pipe marker and restore ground level to original contours as per regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolinc Oil and Gas Company

Address Box 127

Farmington, New Mexico

By L. D. Spruill

Title Production Foreman

[illegible]