



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REGULATIONS

NOTICE OF INTENTION TO DRILL	SUBSECTION
NOTICE OF INTENTION TO CHANGE PLAN	SUBSECTION
NOTICE OF INTENTION TO TEST WATER QUALITY	SUBSECTION
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSECTION
NOTICE OF INTENTION TO SHUT-IN WELL	SUBSECTION
NOTICE OF INTENTION TO PULL OR ALTER Casing	SUBSECTION
NOTICE OF INTENTION TO ABANDON WELL	SUBSECTION

INDICATE ABOVE BY CHECK MARK NATURE OF WORK

APPROVED

3 Gravity **1720** **2X** **462** **2X** **61**

26 is located **26 North** **(N) East** **462** **2X** **61**

Well No. 26 **Puerto Chiquito** **Rio Arriba** **New Mexico**

(See and See No.) (Town) (Range) (Section)

(Field) **7455** (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **61**

DETAILS OF WORK

(State names of and expected depths to productive sands; show sizes, weights, and lengths of proposed casing; indicate including jobs, cements, etc.)

- We propose to drill and complete this well as follows:**
1. Drill a 12 inch hole to 30 feet and cement 30 feet of 10 3/4 inch surface casing from the base of the casing to the surface.
 2. Drill to 2300 feet with cable tools to test the Greenhorn formation. Western Drilling Company contractor.
 3. If oil production is encountered, plug back with gravel, cement 1/2 inch casing on bridge plug, drill out plug, and treat open hole with sandfloc.
 4. If a dry hole, contact the U. S. G. S. at Farmington for plugging instructions.

This is an unorthodox Puerto Chiquito location necessitated by topographic conditions. We are writing the OCC at Santa Fe for approval of this location.

Dr. Sam S. Dunn

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **1312 Main Street**
Address **Lubbock, Texas**

By **Geologist**

Title

