

COPY FOR
STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
SUBMIT IN TRIPLICATE TO
DISTRICT OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. SF 078939-C

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 25, 1954

Well No. Renkoff #1 is located 720 ft. from N line and 2040 ft. from E line of sec. 17

NW NE Section 17
(1/4 Sec. and Sec. No.)

19N
(Twp.)

4W
(Range)

N.M.P.M.
(Meridian)

Wildcat
(Field)

Sandoval
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6641 ft. GL

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Production on this well has levelled off at 1.74 barrels of oil and 53.94 barrels of water. Since there is no other known commercial base, authority is requested to plug and abandon. Present P.B.T.D. 2212.

A cement block will be spotted from 2212' to 2250' and an attempt will be made to pull 7" casing which is set at 2196'. If 7" casing is recovered below Allison member, cement plug will be spotted from top of pipe to 50' above top of Allison (1812 top). If 7" is recovered above Allison member, plug will be spotted at top of shot-off 7". A 100' plug will be placed across top of chacre sand member. A 10" plug will be spotted in the top of 10 3/4" surface casing. A marker on top is to be not less than 4" pipe and not less than 10' long of which 4' shall be above the ground and the remainder in cement. The top of the pipe to be closed with a cap or cement and a plate installed to show as follows: (over)

Company Lowry et al Operating Account

Address P.O. Box 8008

Albuquerque, New Mexico

By E. R. Richardson
E. R. Richardson
Title Assistant General Manager



To show as follows:

Tim G. Lowry
Lowry-Renkoff
720' from North line
2040' from East line
17-19N-4W
Well, Renkoff #1