


# NEW MEXICO OIL CONSERVATION COMMISSION

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

February 7, 1952

Date

Farmington, New Mexico

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Stanolind Oil and Gas Company Huerfano Unit Well No. 1 in the  
Company or Operator Lease

NE/4 of Sec. 21, T. -26-N, R. -10-W, N. M. P. M.,

Wildcat Pool San Juan County.

The dates of this work were as follows: January 31, 1952 to February 5, 1952 (incl.)

Notice of intention to do the work was (~~XXXXX~~) submitted on Form C-102 on January 15, 1952, and approval of the proposed plan was (~~XXXXX~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Notice of Intention to Abandon Well, Form C-102, was approved January 16, 1952. Well was permanently plugged and abandoned as follows: 1. Plugged hole with solid cement from bottom of hole to 1900 feet; 2. Shot off 7" casing at following depths: at 1328 feet, at 1157 feet and at 1035 feet. 1025 feet of 7" casing was recovered; 3. Filled hole with 12 pound mud from 1900 feet to 470 feet; 4. Spotted 30 sacks cement plug from 470 to 385 feet; 5. Filled hole with 12 pound from 385 to 225 feet; 6. February 5, 1952, plugged hole with solid cement from 225 feet to surface of hole; 7. Erected 4' pipe marker and restored ground level to original contours as per regulations.

Witnessed by J. R. Stockton Stanolind Oil and Gas Company Head Roundabout  
Name Company Title

APPROVED:  
OIL CONSERVATION COMMISSION

*Al Green*

Oil and Gas Inspector Dist. #3.

FEB 8 1952

Date

I hereby swear or affirm that the information given above is true and correct.

Name.....

Position Production Foreman

Representing Stanolind Oil and Gas Company  
Company or Operator

Address Box 487, Farmington, New Mexico