

APPROVED
Form 9-831a
(Feb. 1951)

JUL 16 1956

JERRY W. LONG
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office New Mexico
Lease No. 0608 013688
Unit Atlantic

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Water Fracture	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 3, 1956

Well No. 1 is located 1650 ft. from [N] line and 990 ft. from [E] line of sec. 25

NE Section 25 31N 10W RMPM
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M. V. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6492 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-1-56 Total Depth 5628'. P.B.T.D. 5650'. Water fractured Point Lookout perf. int. 5532-5544, 5554-5560, 5591-5601 (4 shots/ft.) w/75,455 gals. water & 59,000# sand. Breakdown pressure none, max. pr. 2550#, avg. tr. pr. 2450#. Inj. rate 45.0 Bbls./min. Flush 8700 gallons.

7-1-56 T.D. 5628'. Temp. B.P. at 5500'. Water fractured Menefee perf. int. 5360-5374, 5394-5404, 5447-5457 (4 shots/ft.) w/39,400 gallons water & 27,580# sand. Max. pr. 4300#, avg. tr. pr. 3000#. Inj. rate 36.0 bbls./min. Flush none.

7-2-56 T.D. 5628'. Temp. B.P. at 5157'. Water fractured Cliff House perf. int. 5038-5052, 5058-5064, 5108-5122 (4 shots/ft.) w/78,000 gals. water & 60,000# sand. Breakdown pressure 2250#, max. pr. 2250#, avg. tr. pr. 1950#. Inj. rate 37.5 bbls./min. Flush 8500 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farlington, New Mexico

By

Title

Petroleum Engineer



