

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other Instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.
SF 078146
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME Newberry	
3. ADDRESS OF OPERATOR PO Box 990, Farmington, NM 87401		9. WELL NO. 2A	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1185'N, 1040'W		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T-32-N, R-12-W NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6100'GR		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Dakota was plugged by setting a retainer at 6684' and squeezing below retainer with 50 sks. cement on January 20, 1977.

The well was evaluated and it is intended to permanently plug and abandon the well by:

Spot plug from approximately 4800' to 5100' across the Mesa Verde and displace 50 sks. behind the casing.

Perf holes at 2750' at base of Pictured Cliffs, spot cement plug from approximately 2250' to 2750' and also displace 50 sks. through perfs at 2750'.

Perf squeeze holes at 1000', spot 50 sks. cement and displace 25 sks. through the perfs.

Perf squeeze holes at base of surface casing, spot 50 sks. and displace 25 sks. through the perfs.

Spot 10 sks. cement plug at surface, install dry hole marker and clean up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Chief Div. Drlg. Engr.

DATE

January 20, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 20 1977

*See Instructions on Reverse Side