

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. 078580-4
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 24, 1951

Catherine F. Moore

Well No. 2A is located 1650 ft. from 131 line and 1650 ft. from 131 line of sec. 8
SW 1/4 Sec. 8 T30-N 1-4-W R4PM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6330 ft. 6330

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Bailed hole dry after drilling shoe with cable tools and tested for water shut-off, found 5' of water section, well squeezed with 150 sacks of cement at 3215 and failed to shut off water and well re-squeezed again 3/10/51 with 200 sacks of cement and water was shut-off. Well was drilled to T.O. of 3357' and shot with 19 1/2 lbs of S.N.C. 3225'-3357' and no gas show after clean out. Well was then shot with 4 cone shots per foot 3020'-50' and 3120'-56' and both zones tested no show of gas. Well is now temporarily abandoned awaiting a casing pulling equipment to recover pipe. When casing is recovered a cement plug will be spotted in top of surface casing with the required 10' of 4" pipe embedded in the cement with 4' above ground level. Well sign will then be installed and location leveled off.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blanco Gas Company
 Address 305 West Main Street
Farmington, New Mexico
 By J. S. McNeill
 Title Superintendent