

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. SF 079691
2. NAME OF OPERATOR EL PASO NATURAL GAS CO.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 87401	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 970'N, 1750'W	8. FARM OR LEASE NAME MUDGE
14. PERMIT NO.	9. WELL NO. 6A
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5916' GL	10. FIELD AND POOL, OR WILDCAT BLANCO MESA VERDE
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11, T-31-N, R-11-W NMPM
	12. COUNTY OR PARISH SAN JUAN
	13. STATE NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/25/77: T.D. 3014'. Ran 74 joints 7", 20#, K-55 intermediate casing, 3002' set at 3014'. Cemented with 466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1400'.

11/29/77: T.D. 5310'. Ran 78 joints 4 1/2", 10.5#, KS casing liner, 2484' set 2826-5310'. Float collar set at 5292'. Cemented with 431 cu. ft. cement. WOC 18 hours.

1/28/78: PBD 5292'. Tested casing to 3500#, OK. Perfed C.H. 4157,4225,4243, 4250,4259,4291,4340,4347,4354,4362,4370,4378,4391,4405,4411,4420' w/ 1 SPZ. Fraced with 55,500# 20/40 sand and 111,000 gallons water. Flushed w/5700 gallons water. Perfed Men. 4465,4476,4498,4507,4525, 4539,4565,4589,4602,4630,4641,4687,4700,4707,4732,4737,4742,4748,4753 w/1 SPZ. Fraced w/57,500# 20/40 sand and 115,000 gallons water. Flushed with 6000 gal. water. Perfed P.L. 4853,4858,4863,4868,4891, 4896,4902,4907,4919,4924,4929,4946,4951,4956,4961,4975,5008,5039,5055, 5088,5115,5130,5152,5178,5219,5260' w/1 SPZ. Fraced with 81,500# 20/40 sand and 163,000 gallons water. Flushed w/6400 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED V. P. Brisco

TITLE: Drilling Clerk

DATE 1/30/78

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

1978