

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other *Water Supply Well - P&A

2. Name of Operator
Dugan Production Corp.

3. Address and Telephone No.
P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
990' FSL - 990' FEL
Sec. 27, T26N, R13W, NMMPM

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 138

9. API Well No.

30-045-95004

10. Field and Pool, or Exploratory Area

* Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Pressure test casing to 500 psi - OK.
2. Run tubing and tag up $\pm 1930'$.
3. Perforate Pictured Cliffs at 1349'.
4. Spot 233 cu. ft. Class B with 4% gel @ 1357'. Pull tubing. Displace cement to 1068'. No flow back. Pictured Cliffs - Fruitland plug 1068' - 1357'.
5. Perforate below surface casing @ 88'.
6. Cement to surface through 9-5/8" casing with 124 cu. ft. Class B with 4% gel. Surface plug @ 88'.

Job complete 6-15-93.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander
(This space for Federal or State office use)

Title Operations Manager

Date 6/16/93

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

DISTRICT MANAGER