	ct State	e of New Mexico	Rec'd	06/22/2020 - NMOC	
Office <u>District I</u> – (575) 393-6161		erals and Natural Res	sources		Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 8824 District II – (575) 748-1283				WELL API NO. 30-025-467	56
811 S. First St., Artesia, NM 88210	11 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION			5. Indicate Type of Leas	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 874	1220 South St. Francis Dr.		•	STATE FEE	
<u>District IV</u> – (505) 476-3460	San	ta Fe, NM 87505		6. State Oil & Gas Lease	e No.
1220 S. St. Francis Dr., Santa Fe, NM 87505				320561	
SUNDRY NOTICES AND REPORTS ON WELLS				7. Lease Name or Unit A	Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				HEMLOCK 32 STATE	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			<u> </u>	0. W. 11. V.	
1. Type of Well: Oil Well	☐ Othe	er		8. Well Number #50	3H
2. Name of Operator EOG RESOURCES				9. OGRID Number 7377	
3. Address of Operator				10. Pool name or Wildcat	
P O BOX 2267, MIDLAND TX 79702				59900 TRIPLE X; BONE SPRING	
4. Well Location					
Unit Letter M			ine and	567 feet from the \(\frac{1}{2}\)	WESI line
Section 32		ip 23S Range 3		NMPM Coun	ty LEA CO
	11. Elevation (Sho	ow whether DR, RKB, I 3661 GL	RT, GR, etc.		
		3001 GL			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
	F INTENTION TO:	_		SEQUENT <u>R</u> EPORT	
PERFORM REMEDIAL WORK			EDIAL WORK		RING CASING
TEMPORARILY ABANDON	☐ CHANGE PLANS			LING OPNS. P AND) A 📗
PULL OR ALTER CASING DOWNHOLE COMMINGLE	☐ MULTIPLE COMP	L	NG/CEMENT	JOB	
CLOSED-LOOP SYSTEM					
OTHER:	_	□ OTHE		L CSG	<u>X</u>
13. Describe proposed or c					
		.15.7.14 NMAC. For N	Multiple Com	npletions: Attach wellbore	e diagram of
proposed completion or recompletion.					
1	1				
02/21/2020 Cast Iron Bridge	•				
1 1	•				
02/21/2020 Cast Iron Bridge Topped w/ 10' sand	•				
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole	e Plug @ 3,990' MD	051' TVD A 0	ccepted	for Record - NM0	OCD
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0	051' TVD A (ccepted	for Record - NM0	OCD
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (e Plug @ 3,990' MD Hole @ 5,009' MD, 5,0	051' TVD A (ccepted	for Record - NM0	OCD
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT	e Plug @ 3,990' MD Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084')	301 110			OCD
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p	pg), Trail w/ 360 sx C	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p	pg), Trail w/ 360 sx C	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p	pg), Trail w/ 360 sx C	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface	lass A (1.37	yld, 14.8 ppg)	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date:	lass A (1.37 e Resume d	yld, 14.8 ppg) rilling 8-3/4" hole, TA the	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date:	lass A (1.37 e Resume d	yld, 14.8 ppg) rilling 8-3/4" hole, TA the	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for Spud Date: 02/02/2	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date:	lass A (1.37 e Resume d	yld, 14.8 ppg) rilling 8-3/4" hole, TA the	well for now
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for Spud Date: 02/02/2	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date:	lass A (1.37 e Resume d	yld, 14.8 ppg) rilling 8-3/4" hole, TA the	
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for Spud Date: 02/02/2 I hereby certify that the information of the strength of the str	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C4 sx cement to surface Rig Release Date: mplete to the best of m TITLE_Sr. Regulate	lass A (1.37 e Resume d y knowledge	yld, 14.8 ppg) rilling 8-3/4" hole, TA the and belief.	e well for now
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx O Test casing to 1,500 psi for Spud Date: 02/02/2 I hereby certify that the information of the strength of the str	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C4 sx cement to surface Rig Release Date: mplete to the best of m TITLE_Sr. Regulate	lass A (1.37 e Resume d y knowledge	yld, 14.8 ppg) rilling 8-3/4" hole, TA the	e well for now
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx C Test casing to 1,500 psi for Spud Date: 02/02/2 I hereby certify that the information of the strength of the str	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date: mplete to the best of m TITLE Sr. Regulate E-mail address: emily	y knowledge	yld, 14.8 ppg) rilling 8-3/4" hole, TA the and belief. stratorDATE ogresources.commone:	e well for now 6-22-2020
02/21/2020 Cast Iron Bridge Topped w/ 10' sand 02/21/2020 12-1/4" hole 02/21/2020 1st Intermediate Casing shoe @ 5,084' MD Ran 9-5/8", 40#, J-55 LTC (Ran 9-5/8", 40#, HCK-55 LT Lead Cement w/ 1,410 sx O Test casing to 1,500 psi for Spud Date: 02/02/2 I hereby certify that the information of the strength of the str	e Plug @ 3,990' MD e Hole @ 5,009' MD, 5,0 (0' - 4,028') TC (4,028' - 5,084') Class A (1.88 yld, 12.9 p 30 min - Good. Circ 454 2020 ation above is true and confidence of the collise follise	pg), Trail w/ 360 sx C 4 sx cement to surface Rig Release Date: mplete to the best of m TITLE Sr. Regulate E-mail address: emily	y knowledge	yld, 14.8 ppg) rilling 8-3/4" hole, TA the and belief. stratorDATE ogresources.commone:	e well for now 6-22-2020