

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD Hobbs

FORM APPROVED  
OMB NO. 1004-0135  
Expires: July 31, 2010

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. NMLC057210
2. Name of Operator CONOCOPHILLIPS COMPANY		6. If Indian, Allottee or Tribe Name
3a. Address 3300 N "A" ST BLDG 6 MIDLAND, TX 79705		7. If Unit or CA/Agreement, Name and/or No NMNM70987A
3b. Phone No (include area code) Ph: 432-688-9171 Fx: 432-688-6019		8. Well Name and No MCA UNIT 480
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 28 T17S R32E SWSE Lot O 1310FSL 1995FEL		9. API Well No. 30-025-39766-00-X1
		10. Field and Pool, or Exploratory MALJAMAR Grayburg, SA-
		11. County or Parish, and State LEA COUNTY, NM

## 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input checked="" type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

ConocoPhillips would like to change the approved APD from drilling as a producer to strictly drilling as an injection well.

Different from the drilling plan was that we RIH w/inj pkr & set @ 3815'.

SUBJECT TO LIKE  
APPROVAL BY STATESEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct.	
Electronic Submission #117343 verified by the BLM Well Information System For CONOCOPHILLIPS COMPANY, sent to the Hobbs Committed to AFMSS for processing by DEBORAH MCKINNEY on 09/13/2011 (11DLM0757SE)	
Name (Printed/Typed) RHONDA ROGERS	Title STAFF REGULATORY TECHNICIAN
Signature (Electronic Submission)	Date 09/12/2011

## THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By DUNCAN WHITLOCK	Title LEAD PET	Date 11/02/2011
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

NOV 09 2011

# **Conditions of Approval**

**ConocoPhillips Company**

**MCA Unit 480**

**API 3002539766**

November 02, 2011

1. Provide an injection casing cement bond log record from plug back total depth to top of cement.
2. Prior BLM approval of a notice of intent (BLM Form 3160-5) is required for fracture treatment of injection wells. The operator will be required to tag fracture material with a tracer and run a tracer survey to verify that the fracture material is not placed out of zone. Results of the tracer to be reported on the workover subsequent sundry Form 3160-5.
3. One year after fracture stimulation an injection profile tracer survey is to be run. Submit the survey report to the BLM Carlsbad Field office in a subsequent sundry Form 3160-5.

## **General Conditions of Approval: Wells with Packers**

- 1) Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
  - a) The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
  - b) Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
  - c) Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
  - d) Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
  - e) Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore workover.
  - f) **Submit the original subsequent sundry with three copies to BLM Carlsbad.**
- 2) Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
  - a) Approved injection pressure compliance is required.
  - b) If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
  - c) When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
    - i) Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
- 3) Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 4) The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
- 5) The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
- 6) **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of beginning injection.
- 7) The operator shall keep monthly records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.
- 8) Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
  - a) Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
- 9) Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for planned well work involving a formation change, casing repair/replacement, and injection well fracture treatment for approval by BLM and NMOCD. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days. Packer and tubing repair (normal maintenance procedures) do not require a NOI, but a subsequent sundry needs to be filed.
- 10) Submit a (Sundry Form 3160-5) subsequent report (daily reports) describing all wellbore activity and Mechanical Integrity Test as per item 1) above. Include the date(s) of the well work, and the setting depths of required equipment: tubing, on/off tool, profile nipple, and packer.

PRS 110211