

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003 WELL API NO. 30-025-36788 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.									
WELL COMPLETION OR RECOMPLETION REPORT AND LOG													
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER			7. Lease Name or Unit Agreement Name Robinson										
2. Name of Operator Trilogy Operating, Inc.			8. Well No. 1										
3. Address of Operator P.O. Box 7606 Midland, Tx. 79708			9. Pool name or Wildcat Nadine-Drinkard- Abo										
4. Well Location Unit Letter L : 1972' Feet From The South Line and 342' Feet From The West Line Section 19 Township 19-S Range 38-E NMPM Lea County													
10. Date Spudded 11/9/04		11. Date T.D. Reached 1/12/05		12. Date Compl. (Ready to Prod.) 3/18/05									
13. Elevations (DF& RKB, RT, GR, etc.) 3575 GR		14. Elev. Casinghead 3575											
15. Total Depth 7900		16. Plug Back T.D. 7300		17. If Multiple Compl. How Many Zones? N/A									
18. Intervals Drilled By X		Rotary Tools X		Cable Tools									
19. Producing Interval(s), of this completion - Top, Bottom, Name Top Drinkard					20. Was Directional Survey Made No								
21. Type Electric and Other Logs Run DIL, CNL					22. Was Well Cored No								
23. CASING RECORD (Report all strings set in well)													
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED								
8 5/8	#24	1618'	12 1/4	850 sxs "C"									
5 1/2	#17	6500'	7 7/8	950 sxs"C" 500sxs"H"									
24. LINER RECORD													
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN									
4"	6350'	7900'	70 sxs"H"										
25. TUBING RECORD													
SIZE	DEPTH SET	PACKER SET											
2 3/8	6910'												
26. Perforation record (interval, size, and number) 7126'-7136' 6952'-7075'													
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="text-align: left;">DEPTH INTERVAL</th> <th style="text-align: left;">AMOUNT AND TYPE OF FLUID USED</th> </tr> <tr> <td>7126-7136</td> <td>2000 gals 5% NEFE</td> </tr> <tr> <td>6952-7075</td> <td>3000 gals 15% NEFE</td> </tr> <tr> <td>6952-7075</td> <td>52,000 gals Xlink gel 10,500 # 1630 Ottawa</td> </tr> </table>						DEPTH INTERVAL	AMOUNT AND TYPE OF FLUID USED	7126-7136	2000 gals 5% NEFE	6952-7075	3000 gals 15% NEFE	6952-7075	52,000 gals Xlink gel 10,500 # 1630 Ottawa
DEPTH INTERVAL	AMOUNT AND TYPE OF FLUID USED												
7126-7136	2000 gals 5% NEFE												
6952-7075	3000 gals 15% NEFE												
6952-7075	52,000 gals Xlink gel 10,500 # 1630 Ottawa												
28. PRODUCTION													
Date First Production 3/19/05		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping 2 x 1 1/2 x 16'			Well Status (Prod. or Shut-in) Prod								
Date of Test 3/24/05	Hours Tested 24	Choke Size n/a	Prod'n For Test Period	Oil - Bbl 25	Gas - MCF 100								
Flow Tubing Press. n/a	Casing Pressure 35 psi	Calculated 24-Hour Rate	Oil - Bbl 25	Gas - MCF 100	Water - Bbl. 40								
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold		Test Witnessed By Michael G. Mooney											
30. List Attachments CNL Log DIL Log													
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief													
Signature		Printed Name Chris Smith		Title Geological Assistant									
E-mail Address csmith1@lx.net		Date 4/04/05											

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1675	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2850	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2960	T. Devonian	T. Menefee	T. Madison
T. Queen 3450	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4354	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5579	T. McKee	Base Greenhorn	T. Granite
T. Paddock 5793	T. Ellenburger	T. Dakota	T.
T. Blinbry 6058	T. Gr. Wash	T. Morrison	T.
T. Tubb 6589	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6801	T. Bone Springs	T. Entrada	T.
T. Abo 7222	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
2500	3120	620	Sandstone, Shale, Anhydrite				
3120	4290	1170	Anhydrite, Dolomite				
4290	4700	410	Dolomite, Anhydrite				
4700	6000	1300	Dolomite, Limestone				
6000	6050	50	Dolomite, Chert				
6050	6280	230	Dolomite, Limestone				
6280	6580	300	Dolomite, Limestone, Chert				
6580	6740	160	Dolomite, Limestone, Chert				
6740	6930	190	Dolomite				
6930	7350	420	Limestone				
7350	7900	550	Dolomite, Limestone				