Submit 3 Copies To Appropriate District State of New Mexico	Form C-103
Office District I Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	WELL API NO.
1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	30-025-37205 5. Indicate Type of Lease
District III 1220 South St. Francis Dr.	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	STATE FEE
1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	State 22
1. Type of Well: Oil Well Gas Well Other	8. Well Number #001
2. Name of Operator	9. OGRID Number
Brigham Oil & Gas, L.P. 3. Address of Operator	163160
6300 Bridge Point Pkwy., Bldg. 2, Ste. 500, Austin, TX 78730	10. Pool name or Wildcat King; Wofcamp
4. Well Location	
Unit LetterJ:2293_feet from the _south_ line and _1569_feet from _1569	om the _eastline
Section 22 Township 13S Range 37E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc. 3879' (GR)	
Pit or Below-grade Tank Application or Closure	
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDis	stance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; C	onstruction Material 181920273
12. Check Appropriate Box to Indicate Nature of Notice,	
	\D
NOTICE OF INTENTION TO: SUE PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	SEQUENT REPORT OF
	RK 🔲 (A) TERING CASING 🗆
TEMPORARILY ABANDON CHANGE PLANS COARAGNOE DE	WILING ODNO EL PLAND A
	ILLING OPNS 🛛 PAND A
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER:	T JOB 🛛 O
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar	T JOB d give pertinent dates, including signated date
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER:	T JOB d give pertinent dates, including signated date
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion.	T JOB d give pertinent dates, including signated date
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05.	IT JOB Id give pertinent dates, including contracted date ttach wellbore diagram of proposed completion
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s	IT JOB Id give pertinent dates, including section of date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687	IT JOB Id give pertinent dates, including connected date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonite.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonite. I with 479 sx Class C mixed at 14.8 ppg and
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including second date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK.	It JOB It give pertinent dates, including contracted date ttach wellbore diagram of proposed completion at Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHE	IT JOB Id give pertinent dates, including contracted date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonite. I with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe are and belief. I further certify that any pit or below.
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: Is details, an of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (I) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK.	It JOB It give pertinent dates, including contracted date ttach wellbore diagram of proposed completion at Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. Sex Class C (50/50 Poz) cmt with 10% bentonite. It with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe for an (attached) alternative OCD-approved plan.
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK. I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □	IT JOB Id give pertinent dates, including settrated date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe for an (attached) alternative OCD-approved plan contact the part of the proposed completion in the proposed com
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK. I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Env/Reg. Saf. Engi	IT JOB Id give pertinent dates, including settrated date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonite. I with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe or an (attached) alternative OCD-approved plan DATE June 1, 2005 Telephone No. (512)427-3300
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK. I hereby certify that the information above is true and complete to the best of my knowledgerade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Env/Reg. Saf. Enginger State Use Only PETROLEUM	IT JOB Id give pertinent dates, including sectrated date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. 5x Class C (50/50 Poz) cmt with 10% bentonited with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe for an (attached) alternative OCD-approved plan contact the proposed completion in t
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. (1) MIRU Big Dog Drilling Rig #1. Spud well @ 7:00 p.m. on 05/04/05. (2) Run 13-3/8" 48# J-55 surface casing to 410' on 05/05/05. Cement with 440 s WOC. Test wellhead to 750 psi. NU BOPs. Test BOP stack and manifold to (3) Run 8-5/8" 24#/32# J-55 ST&C csg to 4767' on 05/15/05. Cement with 687 5% NaCl, 0.25pps Celloflake mixed @ 11.8 ppg and 2.45 cu. Ft/sx yield. Tai 1.33 cu. Ft/sx yield. Had good returns and circulated 90 bbls to surface. WOC manifold and Kelly valves to 3000 psi. Test hydril to 1500 psi. Test csg to 10 joint to 1000 psi. Held OK. I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Env/Reg. Saf. Engi	IT JOB Id give pertinent dates, including settrated date ttach wellbore diagram of proposed completion x Class C with 2% CaCl and 0.25# Flocele. 500 psi. Held OK. sx Class C (50/50 Poz) cmt with 10% bentonite. I with 479 sx Class C mixed at 14.8 ppg and C. NU BOPs. Test blind rams, pipe rams, 00 psi. Drill cement and float collar. Test shoe or an (attached) alternative OCD-approved plan DATE June 1, 2005 Telephone No. (512)427-3300