## This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

Well No. 59

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Operator Williams Exploration and Production Lease Name Rosa Unit

Location Of Well: Unit Letter N Sec 25 Twp 31N Rge 06W

API # 30-0 300392327000

	Name of Reservoir or Pool		Type of Prod.			Method of Prod.	Prod. Medium	
		1.0	(Oil	or Gas)	(F	low or Art. Lift)	(Tbg. Or Csg.)	
Upper	-		1			P./	Appen and a	
Completion	J OL		09	. <b>.</b>	$\rightarrow$	Mour	C55	
Lower Completion	DK		64	645		Clone	Tha	
		F	Pre-Flow Shut-l	In Pressure D	ata		/	
Upper	Hour, Date, Shy	t-In	Length of T	ime Shut-In	SI	Press. Psig	Stabilized? (Yes or No)	
Completion	Hour, Date, Shut-In		72 4rs			326	1/05	
Lower	er Hour, Date, Shut-In		Length of Time Shut-In		SI	Press. Psig	Stabilized? (Yes or No)	
Completion	1110 6	-10-03	/2	hrs		199	yes	
			Flow Te	st No. 1				
Commence	l at (hour, date)* /	110 6-13	5-05	Zone produci	ng (Up	per or Lower):	upper	
Time	Lapsed Time		essure	Prod. 7	Zone	Remarks		
(Hour, Date	) Since*	Upper Compl.	Lower Compl	l. Tem	ıp.			
1110 6-11	4 24 hr	136	195	75				
1110 6-15	- 48 hr	136	191	79	ĵ			
	72hr	136	198	70			(1000.33202)	
							A Lord	
							F: 10.	
							Ve.	
Production rat	e during test							
)il:	BOPD based or	Вь	ls. In	Hrs		Grav	GOR	
Gas:	<u></u> MCFPI	; Test thru (Orif	ice or Meter): _	orio	Ore.		<del></del> .	
		Mi	id-Test Shut-In	Pressure Da	ta			
Upper Completion	Upper Hour, Date, Shut-In					ss. Psig	Stabilized? (Yes or No)	
Lower			Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)	

(Continue on reverse side)

27.7		TET 4	<b>3</b> .7	,
rı	nw.	Test	INO.	

			Plow Test P			18
Commenced a	at (hour, date)**		[ [ Zo	ne producing (U	pper or Lower):	ν.
Time (Hour, Date)	Lapsed Time  Since**		essure Lower Compl. ©	Prod. Zone	Remarks	
		4			1 2 2 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	i birin eri
	* pt - 35 *	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		/	26 AG	3
1. 2m F		the mercial		_		
_	· · · · · · · · · · · · · · · · · · ·					
				3		
roduction rate of il:as:	BOPD based	on O; Test thru (Orifi	Bbls, In ce or Meter):,	Hrs:	Grav	_GOR
emarks: hereby certify t	that the information JUN 20 2		ed is true and comp	lete to the best of	1	
	Conservation Di			By	y Tigh	
tle	TY OIL & GAS INSI	PECTOR, DIST. 48		E-mail Addres	s	
				Date 6	-16-05	

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).