

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 May 27, 2004

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-37114
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name V Laughlin
8. Well Number 6
9. OGRID Number 495
10. Pool name or Wildcat Monument; Abo Southeast (96764)

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
P.O. Box 840 Seminole, TX 79360

4. Well Location
 Unit Letter D : 805 feet from the North line and 350 feet from the West line
 Section 9 Township 20S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3555' GL

Pit or Below-grade Tank Application or Closure

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> OTHER: P&A dry hole <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>	
--	--	---	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/1/2005

Plan to plug and abandon dry hole. Please see attached plugging procedure.

**THE OIL CONSERVATION DIVISION MUST
 BE NOTIFIED 24 HOURS PRIOR TO THE
 BEGINNING OF PLUGGING OPERATIONS.**



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCDC guidelines , a general permit or an (attached) alternative OCD-approved plan .

SIGNATURE Carol J. Moore TITLE Senior Advisor/Regulatory DATE 7/1/2005

Type or print name Carol J. Moore E-mail address: cmoore@hess.com Telephone No. (432)758-6738

For State Use Only
 APPROVED BY: Larry W. Wink TITLE OG FIELD REPRESENTATIVE II/STAFF MANAGER DATE JUL 11 2005

Conditions of Approval (if any):

WELL : LAUGHLIN # 6
 COUNTY: LEA
 AREA : MONUMENT

SURF LOC : SECTION #4, T-20S, R-37E
 350' FWL & 805' FNL
 LEA COUNTY, NEW MEXICO

ENG : Leo Benitez
 RIG : Patterson Rig 707
 RKB : 13'

DEPTH		HOLE SIZE	CASING PROFILE	CASING	MW TYPE	SHOE TEST	Min Cmt Vol
MD	TVD						
60'	60'	Rat Hole Machine	5	CONDUCTOR 16"	N/A	N/A	N/A
1,225'	1,225'	12 1/4"	4 3 2 1	SURFACE CASING 8 5/8" 24.0 ppg J-55 STC	Fresh Water MW : 8.4 - 9.0	12.0 ppg	Est. Top Cmt Surface
P & A PROCEDURE							
Cmt Plugs: (1.33 yield Class C Neat 14.8 ppg)							
No. 1: Top of Fish (2,595') : 30 Sacs (1.33 yield Class C Neat = 116')							
No. 2: 50 Sacs below 8 5/8" Shoe (Cmt Top: 1,225' ; Btm: 1,421')							
No. 3: 50 Sacs inside 8 5/8" (Cmt Top: 1,039' ; Btm: 1,225')							
No. 4: 50 Sacs inside 8 5/8" (Cmt Top: 257' ; Btm: 443')							
No. 5: 10 Sacs @ Surface							
Back OFF @ 2,595'							
Cmt Inside Fish from 2,625' to 4,511'							
Kicked OFF @ 2,886 @ 90 Deg Azi.							
Cement Kick OFF Plug							
TOC : 2,886'							
150 sx (36 BBLs) Class C Neat							
Btm Cmt Plug : 3,145'							
7" Open Hole Whipstock							
TOP Whipstock 3,150'							
Btm Whipstock 3,230'							
4 1/2" DP 16.60 G-105							
TOP Fish : 3,250'							
Bridge Plug : 3,350'							
Btm Fish : 3,810'							
Spot 200 sx (48 BBI) Cmt Inside Fish							
4,407'	4,407'	7 7/8"					

P & A PROCEDURE
Cmt Plugs: (1.33 yield Class C Neat 14.8 ppg)
 No. 1: Top of Fish (2,595') : 30 Sacs (1.33 yield Class C Neat = 116')
 No. 2: 50 Sacs below 8 5/8" Shoe (Cmt Top: 1,225' ; Btm: 1,421')
 No. 3: 50 Sacs inside 8 5/8" (Cmt Top: 1,039' ; Btm: 1,225')
 No. 4: 50 Sacs inside 8 5/8" (Cmt Top: 257' ; Btm: 443')
 No. 5: 10 Sacs @ Surface

Back OFF @ 2,595'
 Cmt Inside Fish from 2,625' to 4,511'

Kicked OFF @ 2,886 @ 90 Deg Azi.

Kick Off Assy. Bit, Bit Sub, 1Jt DP)
 TOP Kick Off Assy.. 3,150'
 Btm Kick Off Assy. 3,184'

Cmt Top: 3,993'

Cmt Btm: 4,511'

4.5" DP @ 4,511'

HOLE Size: 7 7/8"
 TD: 4,597'

