STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## OIL CONSERVATION DIVISION

API#

30-039-07671

Page 1 Revised 10/01/78

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON RESOURCE	LINGTON RESOURCES OIL & GAS CO. Lease SAN JUAN 29-7 UNIT				Well No. 82			
Location —									
of Well:	Unit B Sect	04 Twp.	029N	Rge.	007W	County	RIO ARRIBA		
		RESERVOIR OR POO		<del></del>	PE OF PROD.	- <del></del>	OD OF PROD.	PROD. MEDIUM	
					(Oil or Gas)		w or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	PICTURED CLIFFS				Gas	Flow		Casing	
Lower Completion	MESAVERDE			Gas Artificial			Tubing		
	<del></del>	PRE-I	FLOW SHUT-IN	PRESS	URE DATA				
Upper	Hour, date shut-in	Length of time shut	h of time shut-in SI press. psig Stabi		Stabilized? (Ye	es or No)			
Completion	07/15/2005	72 Ho	urs		205				
Lower Completion	07/15/2005	120 Ho	ours		152				
			FLOW TES	T NO.	1			-	
Commenced	at (hour,date)*	07/18/2005			Zone producing	(Upper or	Lower) UP	PER	
TIMÉ	LAPSED TIME		SSURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Comple	etion	TEMP	REMARKS			
07/19/2005	96 Hours	101	152			Produce Upper zone			
07/20/2005	120 Hours	101 152				Upper zone producing under lower			
						Pack	er Held		
Production rate	e during test	]				<u> </u>			
Oil	BOPD based on Bbl:		in Hou		Grav			GOR	
Gas:		MCFPD; Tested thru	(Orifice or Meter	):					
		AATE	TEST SHIP N	DDESS	LIDE DATA				
Upper Completion	Hour, date shut-in	MID-TEST SHUT-IN I						es or No)	
Lower Completion	Hour, date shut-in	Length of time shut-in		SI p	SI press. psig		Stabilized? (Y	es or No)	

6968502 401

(Continue on reverse side)

^,

FLOW TEST NO. 2

Commenced at (hour, dat	te)**			Zone producing (Upper or Lower):				
TIME	LAPSED TIME SINCE "	PRESSURE		PROD. ZONE	REMARKS			
(hour, date)		Upper Completion	Lower Completion	TEMP.	NEMBURG			
		, ,			* .			
			· · ·					
				İ				
	-				Maria Cara de Maria de Cara de			
				,				
· •-								
Production rate duri	ing test							
Oil:	ВО	PD based on	Bbls. in	Hours	GravGOR			
					11			
Remarks:								
I hereby certify that	the information her	ein contained is true	and complete to th	ne best of my knowled	70			
	_				ge.			
		<b>19</b>		Operator Burlingt	ton Resources			
New Mexico Oil	Conservation Divis	ion		By Charge	llows			
ву Д. у	illanu	eva		Title Operations A	Associate			
	OIL & GAS INSPEC	TOR, DIST. 🚜	<del></del>	Date Thursday, July 28, 2005				
· · ·								

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on a minitial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
  24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).