

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-041-10048
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator J. CLEO THOMPSON		6. State Oil & Gas Lease No. 26365
3. Address of Operator 325 N. ST. PAUL, SUITE 4300, DALLAS, TX 75201		7. Lease Name or Unit Agreement Name: MILNESAND UNIT
4. Well Location Unit Letter <u>O</u> : 660 feet from the <u>SOUTH</u> line and <u>1980</u> feet from the <u>EAST</u> line Section <u>5</u> Township <u>8S</u> Range <u>35E</u> NMPM County <u>R00SEVELT</u>		8. Well No. <u>14</u>
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4237' GL		9. Pool name or Wildcat MILNESAND (SAN ANDRES)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒	REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐
OTHER: REPAIR INJECTION WELL ☐	OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- 1.) SET CIBP @ 4500'. SPOT 3 SXS CEMENT. WAIT ON CEMENT & TAG PLUG.
- 2.) RIH WITH TBG. CIRCULATE 9.5# SALT MUD TO SURFACE.
- 3.) RU WIRELINE. PERFORATE 2 HOLES AT 2215' AND 2 HOLES @ 475'. RD WIRELINE.
- 4.) RIH W/TBG AND PACKER. SET PACKER @ 2200' AND SQUEEZE WITH 80 SACKS CLASS "C" NEAT CEMENT. (AS PER DAVID GLASS, BLM 6/5/03). TAG PLUG.
- 5.) PU, SET PACKER @ 460', SQUEEZE WITH 25 SACKS CEMENT. FLUSH TO PACKER. UNSEAT PACKER. SPOT 25 SACKS CEMENT.
- 6.) PULL UP TO 250' & REVERSE. POOH WITH PACKER. TAG CEMENT PLUG. POOH. SET 10 SACKS SURFACE PLUG.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jim Stevens TITLE OPERATIONS MANAGER DATE 06/11/2003
Type or print name JIM STEVENS Telephone No. (432)550-8887

(This space for State use)

APPROVED BY Gary W. Wink TITLE FIELD REPRESENTATIVE II/STAFF MANAGER DATE JUN 17 2003
Conditions of approval, if any:

PLUGGING & ABANDONMENT WORKSHEET (2 STRING CSNG)

OPERATOR J. Cleo Thompson
LEASENAME MILNESAND UNIT
WELL # 14
SECT 14 **TWN** 8S **RNG** 35E
FROM 660 **SL** 1980 **E** L
TD: 4719' **FORMATION @ TD** San Andres
PBTD: 4712' **FORMATION @ PBTD** San Andres

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	8 5/8	425'	Surface	Circulated
INTMED 1				
INTMED 2				
PROD	4 1/2	4713'	3915'	Temp Survey
	SIZE	TOP	BOT	TOC DETERMINED BY
LINER 1				
LINER 2				
	CUT & PULL @		TOP - BOTTOM	
INTMED 1			PERFS	4552' - 4712'
INTMED 2			OPENHOLE	-
PROD				

*REQUIRED PLUGS DISTRICT I

MUTLER (AMITY)	
YATES	
QUEEN	
GRAYBURG	
SAN ANDRES	
CAPTAN REEF	
DELAWARE	
BELL CANYON	
CHERRY CANYON	
BRUSHY CANYON	
BONE SPIND	
GLORITA	
BLINDEY	
TUBB	
DRENCARD	
ABO	
WC	
PENN	
STRAWN	
ATOKA	
MORROW	
WIS	
DEVONIAN	

PLUG	TYPE PLUG	SACKS CMNT	DEPTH
EXAMPLES			
PLUG #1	OH	35 SXS	6400'
PLUG #2	SHOE	50 SXS	5350'-5450'
PLUG #3	CIBP/35'		4800'
PLUG #4	CIBP	25 SXS	4800'
PLUG #5	STUB	50 SXS	3600'-3700'
PLUG #6	REINR SOZ	200 SXS	400'
PLUG #7	SURF	10 SXS	0-10'
PLUG #1	CIBP	35 SXS	4489'
PLUG #2	Salt	80 SXS	2215'-2033'
PLUG #3	Shoe	50 SXS	385'-475'
PLUG #4	Surf	10 SXS	0-10'
PLUG #5			
PLUG #6			
PLUG #7			
PLUG #8			
PLUG #9			
PLUG #10			
PLUG #11			
PLUG #12			
PLUG #13			
PLUG #14			
PLUG #15			
PLUG #16			

8 5/8"
@ 425'
TOC surface

San Andres Perfs
4552' - 4712'

4 1/2"
@ 4713'
TOC 3915'

TD 4719'

