

WELLBORE SCHEMATIC

30-025-11720

South Justis Unit E #22

(Amerada Petr Corp, Ida Wimberley #4)
660' FSL & 990' FWL (Unit M)
Sec 24, T-25S, R-37E, Lea Co., NM
API 30-025-11720
KB-3081', GL-3070', KB-11'
Spudded 05/30/58
Completed 06/30/58

Type Log For SJU

17-1/2" Hole.
13-3/8" 36# casing @ 497'.
Set w/400 sxs cmt. Circ.

TOC @ 1650' by TS.

12-1/4" Hole.
9-5/8" 40# N-80, J-55 & 36# J-55 @ 3269'.
Cmt w/ 1500 sxs

TOC @ 3350' by TS

Tight Spots @ 5138' & 5188'

CIBP @ 4950' w/ 25'cmt (4925'PBTD)

Blinbry Perfs
4981'- 5584'

CIBP @ 5600' w/ 10'cmt (5590' PBTD)
5609' -Blinbry- Perf (1 Single Perf)
5658'-72' - Tubb Perfs

CIBP @ 5700' w/ 10'cmt (5690' PBTD)
5719'-Top of Cmt Plug (no record of plug)
5886'- 5942' - Drinkard Perfs

Cmt Ret @ 6050'
Sqz w/ 55 sxs Class C Cmt

Bad Csg-6202'-6361'

Top of 2 3/8" tbg fish @ 6527

Model D pkr @ 6760'

5-1/2" 15.5# J-55 Liner @ 6730' to 6996'
Cmt w/ 65 sxs, TOC @ 6730'

8-3/4" hole.
7" csg @ 6828'
23# J-55 (0'-5290'), 23# N-80 (5290'-6828')
Cmt w/ 465 sxs

6830' to 6916' - Fusselman Perfs
OH sqzd w/cmt @ 6900'
5-1/2" 15.5# J-55 Liner @ 6996'

Fusselman OH @ 6828' to 7000'

SEP 23 2014