District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (\$75) 393-6161 Fax: (575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe. NM 87505

Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

District III 1000 Rio Brazos Roa	d. Aztec. NM 87	410		1220 South St. Francis Dr.						District Office	
Phone: (505) 334-617 District IV 1220 S. St. Francis D	78 Fax: (505) 33-	1-6170	Santa Fe, NM 87505						☐ AMENDED REPORT		
Phone: (505) 476-346		5-3462	WELLIO	AC A TIO		DE A CE D	EDICA	TIONI DI A	Tr.		
	\	WELL LO	² Pool Code		EAGE DEDICATION PLAT ³ Pool Name						
		4500				BAISH; WOLFCAMP NORTH					
⁴ Property	Code	⁵ Property Name							⁶ Well Number		
OGRID.	No	LANDSDALE "D" FEDERAL COM 8 Operator Name							l ⁹ Elevation		
4323		CHEVRON U.S.A. INC.								Bievation	
-					[™] Surface	Location	 				
UL or lot no.	i	Township	Range	Lot Idn	Feet from the			Feet from the	East/West line	County	
I 	4	19S	32E		1980	SOUTI		660	EAST	LEA	
¹¹ Bottom Hole Location If Different From Surface											
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/So	uth line	Feet from the	East/West line	County	
12 Dedicated Acr	es ¹³ Joint o	r Infill	Consolidation (Code 15 Or	der No.						
40		1		}							
											
No allowable division.	will be ass	signed to t	ihis complet:	ion until a	II interests have	been consol	idated or	a non-standai	rd unit has been app	proved by the	
16				-,							
								ll l	PERATOR CERT of that the information contained		
					1			to the hest of my knowledge and belief, and that this organization either			
								owns a workin	g interest or unleased mineral in	tterest in the land including	
								1	nottom hole location or has a rig		
								11	ant to a contract with an owner or a voluntary pooling agreement o	-	
								ii .	re entered by the division.		
		1						Althis	e VineKerto	D ^{07/25/2014}	
								Signature		Date	
								DENISE PIN	DENISE PINKERTON REGULATORY SPECIALIST		
								Printed Name	:		
								<u>leakeid@che</u> E-mail Addre	vron.com		
						, ,		L-man Addic			
						1		*SURV	EYOR CERTI	FICATION	
					/	* (m dot	LIN	ertify that the well locat		
						`		. خلا	lotted from field notes o	•	
								ll .	ie or under my supervis		
								same is tri	ie and correct to the bes	st of my belief.	
							1,	Det eff			
						_		Date of Surv	ey ad Seal of Professional Surve	evor.	
						1 3		Signature all	e sear or reseasionar sm w	-joi.	
						1 %					
										:	
		l					ľ	Certificate N	umber :		

Landsdale D Federal Com 1 30-025-26256 Chevron USA Inc. Conditions of Approval

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken:
Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually.
During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Notify BLM at 575-393-3612 a minimum of 24 hours prior to commencing work.

Work to be completed by September 9, 2015.

- 1. Operator shall pump approximately 50 sx Class H cement (CIBP is optional) from the top of the packer at 12,500' to 12,125' (Top of Morrow at 12,174'). Tag required.
- 2. Must conduct a casing integrity test before perforating and fracturing. Submit results to BLM. The CIT is to be performed on the production casing to max treating pressure. Notify BLM if test fails.
- 3. Before casing or a liner is added or replaced, prior BLM approval of the design is required. Use notice of intent Form 3160-5.
- 4. Surface disturbance beyond the originally approved pad must have prior approval.
- 5. Closed loop system required.
- 6. All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of work over operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.
- 7. Operator to have H2S monitoring equipment on location.

- 8. Subsequent sundry required detailing work done, a C-102 form, and completion report for the new formations. Operator to include well bore schematic of current well condition when work is complete.
- 9. See attached for general plug back requirements.
- 10. Communitization Agreement NMNM-72059 must be terminated upon completion plug back operations.

CRW 060915

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Production Zone Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from this approval.

If you are unable to plug back the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged back. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plug back operations. For wells in Eddy County, call 575-361-2822. For wells in Lea County, call 575-393-3612
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either **Neat** Class "C", for up to 7,500 feet of depth or **Neat** Class "H", for deeper than 7,500 feet plugs.

6. <u>Subsequent Plug back Reporting:</u> Within 30 days after plug back work is completed, file one original and three copies of the Subsequent Report, Form 3160-5 to BLM. The report should give in detail the manner in which the plug back work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date work was completed.</u>

