' Form 3160-5 (August 1999)

## **OCD-HOBBS**

**UNITED STATES** DEPARTMENT OF THE INTERIOR FORM APROVED OMB NO. 1004-0135 EXPIRES: NOVEMBER 30, 2000

BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an 5. Lease Serial No.

abandoned well. Use Form 3160-3 (APD) for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE	
	7. Unit or CA Agreement Name and No.
1a. Type of Well Oil Well Gas Well Other	8 Well Name and No.
2. Name of Operator	
DEVON ENERGY PRODUCTION COMPANY, LP	Arena Roja Federal 1  9. API Well No.
3. Address and Telephone No.	30-025-37257
20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-8198	10. Field and Pool, or Exploratory
4. Location of Well (Report location clearly and in accordance with Federal requirements)*	Morrow Wildcat
NWSE 1980 FSL 1980 FEL	12. County or Parish 13. State
Sec 27 T26S R35E	Lea NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, TYPE OS SUBMISSION TYPE OF	
	ACTION
	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity
	Recomplete
Final Abandonment Notice Change Plans Plug and Abandon	Temporarily Abandon Operations
Convert to Injection Plug Back  13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of states.	Water Disposal
Drilling Operations 10/20/05-12/18/05:	
Drilling Operations 10/20/05-12/18/05:  Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.	T&L casing and set at 16,744' (46 jts of T-95 from 13,038' d condition mud and hole. Cement liner with lead 475
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.	T&L casing and set at 16,744' (46 jts of T-95 from 13,038 d condition mud and hole. Cement liner with lead 475
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.  14. Vhereby certify that the foregoing is true and correct  Name  Norvella Adams	d condition mud and hole. Cement liner with lead 475
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.  14. Whereby certify that the foregoing is true and correct  Name Norvella Adams Title Sr. Staff Engineering Tech	d condition mud and hole. Cement liner with lead 475
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.  14. Vinereby certify that the foregoing is tipe and correct    Name   Norvella Adams   Signed   Signed	nician Date 12/29/2005
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.  14. Vinereby certify that the foregoing is fine and correct  Signed  Name  Norvella Adams  Title  Sr. Staff Engineering Technology by Contributions of approval, if any A N 1 2006  Title	nician Date 12/29/2005  Date
Continued drilling. TD well at 16, 748'. TOH for liner. Ran in 84 jts of 5", 23.30#, Q-125 and T-95 S 15,095' and 38 jts of Q-125 ST&L from 15,095'-16,744'). 5" liner top packer at 13,004'. Circulate and sacks Class H sand. Test liner top to 1500# - ok. Release rig.  14. Vinereby certify that the foregoing is 1794 and correct  Signed  Name  Norvella Adams  Title  Title  Sr. Staff Engineering Techs  Approved by  Title	nician Date 12/29/2005