

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMNM112279

6. If Indian, Allottee or Tribe Name

7. Permit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

EOG RESOURCES, INC. /

Contact: STAN WAGNER

E-Mail: stan_wagner@eogresources.com

8. Well Name and No.

HOUND 30 FED 704H /

9. API Well No.

30-025-43591

3a. Address

ATTN: STAN WAGNER P.O. BOX 2267
MIDLAND, TX 79702

3b. Phone No. (include area code)

Ph: 432-686-3689

10. Field and Pool or Exploratory Area

WC-025 S253336D UPPER WC

4. Location of Well (Footage, Sec., T., R., M. or Survey Description)

Sec 30 T25S R34E Mer NMP NESW 2283FSL 1995FWL /

11. County or Parish, State

LEA COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original APD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

EOG requests a change in the production casing for this well due to pipe availability.

Change 5-1/2", 23#, HCP110 VAM TOP HT TO: 5-1/2", 20#, ECP110 VAM TOP HT

Change 5-1/2", 20#, HCP110 VAN SG TO: 5-1/2", 23#, HCP110 VAM SFC

Casing Spec Sheets attached.

- All previous COAs will apply. Additional COA is not required.

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #371744 verified by the BLM Well Information System
For EOG RESOURCES, INC., sent to the Hobbs

Name (Printed/Typed) STAN WAGNER

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 03/30/2017

APPROVED

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Mustafa Hagne

Title

PETROLEUM ENGINEER

Date 3/31/2017

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

**BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ****

KZ

Connection Data Sheet

OD	Weight	Wall Th.	Grade	API Drift	Connection
5 1/2 in.	20.00 lb/ft	0.361 in.	P110 EC	4.653 in.	VAM® TOP HT

PIPE PROPERTIES

Nominal OD	5.500 in.
Nominal ID	4.778 in.
Nominal Cross Section Area	5.828 sqin.
Grade Type	High Yield
Min. Yield Strength	125 ksi
Max. Yield Strength	140 ksi
Min. Ultimate Tensile Strength	135 ksi

CONNECTION PROPERTIES

Connection Type	Premium T&C
Connection OD (nom)	6.071 in.
Connection ID (nom)	4.715 in.
Make-up Loss	4.382 in.
Coupling Length	10.748 in.
Critical Cross Section	5.828 sqin.
Tension Efficiency	100 % of pipe
Compression Efficiency	80 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCES

Tensile Yield Strength	729 klb
Compression Resistance	583 klb
Internal Yield Pressure	14360 psi
External Pressure Resistance	12090 psi
Max. Bending with Sealability (CAL IV)	20 °/100 ft
Max. Load on Coupling Face	388 klb


FIELD TORQUE VALUES

Min. Make-up torque	10850 ft.lb
Opti. Make-up torque	11950 ft.lb
Max. Make-up torque	13050 ft.lb
Field Liner Max	15900 ft.lb


VAM® TOP HT (High Torque) is a T&C connection based on the main features of the VAM® TOP connection

This connection provides reinforced torque capability for liners and where High Torque is anticipated due to string rotation during running operations (torque rotating liner while running, rotating casing when cementing). It has been tested as per ISO13679 CAL IV requirements.

VAM® TOP HT is interchangeable with VAM® TOP product line with



VAM® SFC



O.D.	WEIGHT	WALL	GRADE	DRIFT
5.500	23.00	0.415	P110HC	4.545

PIPE BODY PROPERTIES

Material Grade	P110HC
Min. Yield Strength	110 ksi
Min. Tensile Strength	125 ksi
Outside Diameter	5.500 in
Inside Diameter	4.670 in
Nominal Area	6.630 sq.in.
Yield Strength	729 kips
Ultimate Strength	829 kips
Min Internal Yield	14,530 psi
*High Collapse	15,310 psi

P110HC pipe supplied by Tubos Reunidos Seamless

Contact: tech.support@vam-usa.com

Ref. Drawing: ST-D 1220 Rev.A

Date: 30-Mar-17

Time: 12:46 PM

CONNECTION PROPERTIES

Connection OD	5.701 in
Connection ID	4.611 in
Make up Loss	5.446 in
Box Critical Area	4.858 sq.in.
%PB Section Area	73.3%
Pin Critical Area	4.909 sq.in.
%PB Section Area	74.0%
Yield Strength	534 kips
Parting Load	607 kips
Min Internal Yield	14,530 psi
*High Collapse	15,310 psi
Wk Compression	374 kips
Max Pure Bending	20 °/100 ft

TORQUE DATA ft-lb

min	opt	max
10,400	11,600	12,800

Max. Torque with Sealability: 14,080 ft-lb



All information is provided by VAM USA or its affiliates at user's sole risk, without liability for loss, damage or injury resulting from the use thereof; and on an "AS IS" basis without warranty or representation of any kind, whether express or implied, including without limitation any warranty of merchantability, fitness for purpose or completeness. This document and its contents are subject to change without notice. In no event shall VAM USA or its affiliates be responsible for any indirect, special, incidental, punitive, exemplary or consequential loss or damage (including without limitation, loss of use, loss of bargain, loss of revenue, profit or anticipated profit) however caused or arising, and whether such losses or damages were foreseeable or VAM USA or its affiliates was advised of the possibility of such damages.