

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-35891

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

LAUGHLIN

8. Well Number
007

9. OGRID Number
162683

10. Pool name or Wildcat
MONUMENT; TUBB

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
CIMAREX ENERGY CO. OF COLORADO

3. Address of Operator
600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701

4. Well Location

Unit Letter: K : 1650 feet from the SOUTH line and 1875 feet from the WEST line
Section 04 Township 20S Range 37E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3573' - KB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT

REMEDIAL WORK
COMMENCE DRILLING OPNS.
CASING/CEMENT JOB

INT TO PA fm
P&A NR _____
P&A R _____

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) SET 4-1/2" CIBP @ 6,450'; PUMP 25 SXS. CMT. @ 6,450'-6,200'; CIRC. WELL W/ M.L.F.
- 2) PUMP 25 SXS. CMT. @ 5,313'-5,163' (T/GLOR.)
- 3) PUMP 35 SXS. CMT. @ 3,877'-3,570' (DV TOOL, T/G.B.); WOC X TAG CMT. PLUG.
- 4) PUMP 40 SXS. CMT. @ 2,848'-2,518' (T/7-R, T/YATES); WOC X TAG CMT. PLUG.
- 5) PUMP 25 SXS. CMT. @ 1,361'-1,176' (8-5/8" CSG. SHOE, T/SALT); WOC X TAC CMT. PLUG.
- 6) ~~MIX~~ X CIRC. TO SURF. 15 SXS. CMT. @ 100'-3'. ATTEMPT TO PERF + SQZ
- 7) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER.

*Pressure test csg.
check bradenhead for
pressure or flow*

VERIFY CMT ALL STRINGS

DURING THIS PROCEDURE WE USED THE CLOSED-LOOP SYSTEM WITH A STEEL TANK AND HAULED CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Spud Date:

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David A. Eyler TITLE: AGENT

DATE: 09/29/17

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM

PHONE: 432.687.3033

For State Use Only

APPROVED BY: Mark Whitaker TITLE: Petroleum Engr. Specialist DATE: 10/05/2017

Conditions of Approval (if any):



KB: 17' above GL

Cimarex Energy Co. of Colorado

Laughlin #7 (Monument Field)

2310' FNL & 1820' FWL

Sec. 4, T-20S, R-37E, Lea Co., NM

H. Eads

6/5/2012

Updated 9/9/16 by S.Hanford

12-1/4" Hole

8-5/8" 24# J-55 csg @ 1311' - 30 jts
cmtd w/ 620 sx, 143 sx cmt circ

DV Tool @ 3827'

Rods : 167 - 3/4" D rods
90 - 7/8" D rods

Pump: 2-3/8" X 1-1/4" X 16' RHBC

207 jts 2-3/8" 4.7# 8rd J-55 Tbg

Tubb perfs:
(6492' - 6498')
(6574' - 6580')

7-7/8" Hole

4-1/2", 11.6# N-80 csg @ 6800' - 160 jts
cmt w/ 1150 sx (Stg 1: 600, circ 43 & Stg 2: 550, no circ)

PBTD @ 6729'

TD @ 6800'



KB: 17' above GL

Cimarex Energy Co. of Colorado

Laughlin #7 (Monument Field)

2310' FNL & 1820' FWL

Sec. 4, T-20S, R-37E, Lea Co., NM

H. Eads 30-025-35891

6/5/2012

Updated 9/9/16 by S. Hanford

T/SALT ~ 1,226'
T/YATES ~ 2,568'
T/7-R. ~ 2,798'
T/G.B. ~ 3,620'
T/GHOR. ~ 5,238'

12-1/4" Hole

8-5/8" 24# J-55 csg @ 1311' - 30 jts
cmtd w/ 620 sx, 143 sx cmt circ

CIRC. 15 SXS. @ 100'-3'

Pump 25 SXS. @ 1,361'-1,176' - TAG

Pump 40 SXS. @ 2,848'-2,518' - TAG

DV Tool @ 3827'

Pump 35 SXS. @ 3,877'-3,570' - TAG

Pump 25 SXS. @ 5,313'-5,163'

Pump 25 SXS. @ 6,450'-6,200'

SET 4 1/2" CIBP @ 6,450'

Tubb perms:

(6492' - 6498')

(6574' - 6580')

4-1/2", 11.6# N-80 csg @ 6800' - 160 jts

cmt w/ 1150 sx (Stg 1: 600, circ 43 & Stg 2: 550, no circ)

7-7/8" Hole

PBTD @ 6729'

TD @ 6800'

JAE 09/22/17