

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised July 18, 2013

<b>WELL API NO.</b> <b>30-025-45328</b>	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name <b>Speedy 16 State Com</b>	
8. Well Number <b>301H</b>	
9. OGRID Number <b>7377</b>	
10. Pool name or Wildcat <b>Red Tank; Bone Spring East</b>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3570 GR</b>	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input checked="" type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input checked="" type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/26/18 Spud 17-1/2" hole  
Run 13-3/8", 54.5#, J55 STC (0'-1175')  
Cmt lead 896 sx, 13.5 ppg, 1.76 yld  
Tail 153 sx, 14.8 ppg, 1.36 yld  
Test to 1500 psi/30 min - good  
Circ 510 sx to surface  
Resume drilling 12-1/4" hole

Spud Date:

11/26/18

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Renee Jarratt*  
Renee Jarratt

TITLE

Regulatory Analyst

DATE

11/28/18

Type or print name

E-mail address:

PHONE:

432-686-3644

For State Use Only

APPROVED BY:

*[Signature]*

TITLE

Petroleum Engineer

DATE

12/07/18

Conditions of Approval (if any):