Submit 1 Copy To Appropriate District Office	State of New Mexico		Form C-103	
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and	Natural Resources	WELL API NO.	Revised August 1, 2011
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		30-015-00987	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410			5. Indicate Type of Lease	
District IV – (505) 476-3460 Santa Fe, NM 875		IM 8/303	STATE X	FEE /
1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Artesia Metex Unit	/
PROPOSALS.)	/oc Wall Other INIECTIO	TIMES OCD	8. Well Number 056	
1. Type of Well: Oil Well Gas Well Other INJECTION OBBS OCD 2. Name of Operator			9. OGRID Number	
State of New Mexico formerly Car	nyon E&P Company	DEC 052018	269864	/
3. Address of Operator			10. Pool name or Wildcat	
1625 N. French Drive Hobbs, NM 88240 RECEIVED			Artesia QU-GB-SA	
4. Well Location				
Unit LetterA:	330feet from the	North line and3	330feet from the _	_Eastline
Section 35	Township 185	<u></u>	NMPM Eddy	County
。1912年 · 1914年 · 1914	11. Elevation (Show wheth	er DR, RKB, RT, GR, etc.)		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
I hereby certify that the information	above is true and complete to	the best of my knowledge	e and belief.	
SIGNATURE	TITLE		DATE	
Type or print name For State Use Only		ddress:	PHONE:	

Whitalu TITLE P.E.S. DATE 12/05/2018

APPROVED BY: Conditions of Approval (if any):

Canyon E&P Company Artesia Metex Unit #56 30-015-00987 330 FNL & 330 FEL UL-A, Sec 35, T18S, R27E

8 5/8" csg at 490' w/50 sx cmt 5 ½" 14# csg at 1855'. Cemented with 40 sx. Open Hole 1855'-2020'

- 2. Make gauge ring run and set 5 ½" CIBP at 1785'
- 3. Circulate MLF and test casing to 500#.
- 4. Spot 50 sx cmt on top of CIBP
- 5. Perforate 5 $\frac{1}{2}$ " casing at 540' and pump sufficient cement to circulate cement inside and outside of 5 $\frac{1}{2}$ " casing.
- 6. Cut off wellhead 3' below ground level and verify cement is to surface on all strings.
- 7. Install upright marker and cut off anchors.

State of New Mexico for Canyon E&P Company Artesia Metex Unit #56 API 30-015-00987 WBD Before PA 8 5/8" casing set at 490' Cemented w/50 sx 5 1/2" 14# casing set at 1855' 40 sx cement Open Hole 1855'-2020'

State of New Mexico for Canyon **E&P** Company Artesia Metex Unit #56 API 30-015-00987 WBD After PA 8 5/8" casing set at 490' Cemented w/50 sx Perforate 5 1/2" casing at 540' and circulate cement to surface Set 5 1/2" CIPB @ 1755' and spot 50 sx cmt on top 5 1/2" 14# casing set at 1855' 40 sx cement Open Hole 1855'-2020'