Office District I En	State of New Mexico	Form C-103
District 1	ergy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 30-015-34892
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210 O	IL CONSERVATION DIVISION	5. Indicate Type of Lease
District III	1220 South St. Francis Dr.	STATE STEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM		
87505 SUNDRY NOTICES AN	ID REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO I	DRILL OR TO DEEPEN OR PLUG BACK TO A	
DIFFERENT RESERVOIR. USE "APPLICATION F PROPOSALS.)	OR PERMIT" (FORM C-101) FOR SUCH	Roberts 13
	ll 🗌 Other	8. Well Number 1Y
2. Name of Operator		9. OGRID Number 004115
Chaparral Energy, LLC		10. Pool name or Wildcat
3. Address of Operator 701 Cedar Lake Blvd., OKC, OK 73114		Riverside; Morrow
4. Well Location		
	feet from the North line and	1620 feet from the East line
Section 13	Township 17S Range 26E	NMPM Eddy County
	evation (Show whether DR, RKB, RT, GR, et	
	GL, 3325' KB, 3323' DF	
Pit or Below-grade Tank Application 🗌 or Closure	П	
Pit typeDepth to Groundwater	Distance from nearest fresh water well D	istance from nearest surface water
Pit Liner Thickness: mil Belo	ow-Grade Tank: Volume bbls;	Construction Material
TEMPORARILY ABANDON	AND ABANDON REMEDIAL WO COMMENCE DI CASING/CEME	RILLING OPNS. P AND A
OTHER:	OTHER:	and give pertinent dates, including estimated date
of starting any proposed work). SE or recompletion.	E RULE 1103. For Multiple Completions: A	Attach wellbore diagram of proposed completion
or recompletion. 1. Drilled to 8890' 06/22/06.		Attach wellbore diagram of proposed completion
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88	390'.	
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba	390'. sin Super "H" cement + .5% LAP-1, .4% CF	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt,
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 lbm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix	390'. sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix 06/22/06. Displ plug w/205 bbls 10 slurry. Maintained full returns through	sin Super "H" cement + .5% LAP-1, .4% CF ked @ 13.2, 1.65 yld. Disp press 100, max p # Brine w/2% KCl. Pumped 1000 gals mud ughout job. Calculated top of cement @ 650	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sys scavenger cmt ahead of lead
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix 06/22/06. Displ plug w/205 bbls 10 slurry. Maintained full returns through	sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p # Brine w/2% KCl. Pumped 1000 gals mud ughout job. Calculated top of cement @ 650 true and complete to the best of my knowled cording to NMOCD guidelines \(\Bar{\texts}\), a general permit [R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sxs scavenger cmt ahead of lead 0'.
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mix 06/22/06. Displ plug w/205 bbls 10 slurry. Maintained full returns through the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been/will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed or closed according to the stank has been will be constructed to the stank has been will be construct	Sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p p# Brine w/2% KCl. Pumped 1000 gals mudughout job. Calculated top of cement @ 650 true and complete to the best of my knowled cording to NMOCD guidelines □, a general permit [TITLE ENGINEERING.	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sxs scavenger cmt ahead of lead 0'.
or recompletion. 1. Drilled to 8890' 06/22/06. 2. Set 199 jts 5-1/2", 17# casing @ 88 3. Cemented with 610 sxs Permian Ba .4% HR-7, .25 Ibm D-Air 3000, mir 06/22/06. Displ plug w/205 bbls 10 slurry. Maintained full returns through	Sin Super "H" cement + .5% LAP-1, .4% CF xed @ 13.2, 1.65 yld. Disp press 100, max p p# Brine w/2% KCl. Pumped 1000 gals mudughout job. Calculated top of cement @ 650 true and complete to the best of my knowled cording to NMOCD guidelines □, a general permit [TITLE ENGINEERING.	R-3w/o defoamer, 5 Ibm Gilsonite, 3 Ibm Salt, ress 1630. Float held, plug down @ 6:00 p.m. flush & 50 sxs scavenger cmt ahead of lead 0'. 1