

Submit to Appropriate District Office
 State Lease - 6 copies
 Fee Lease - 5 copies
 District I
 1625 N. French, Hobbs, NM 88240
 District II
 811 South First, Artesia, NM 87210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-105
 Revised March 25, 1999

OIL CONSERVATION DIVISION
 2040 South Pacheco
 Santa Fe, NM 87505

WELL API NO. 30-025-36130
5. Indicate Type Of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input checked="" type="checkbox"/> OTHER _____	7. Lease Name or Unit Agreement Name Brabant
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER	
2. Name of Operator OXY USA WTP Limited Partnership	8. Well No. 192463 1
3. Address of Operator P.O. Box 50250 Midland, TX 79710-0250	9. Pool name or Wildcat Undsg Brunson Drinkard-Abo, South

4. Well Location
 Unit Letter G : 1980 Feet From The north Line and 1980 Feet From The east Line
 Section 8 Township 22S Range 38E NMPM Lea County

10. Date Spudded 5/31/03	11. Date T.D. Reached 6/28/03	12. Date Compl. (Ready to Prod.) -	13. Elevations (DF & RKB, RT, GR, etc.) 3389'	14. Elev. Casinghead
15. Total Depth 10528'	16. Plug Back T.D. 10380'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools X	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name ---				20. Was Directional Survey Made No
21. Type Electric and Other Logs Run CZDL/DSL/DAL/CNL				22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	54.5#	1300'	17-1/2"	1325sx-Surface	N/A
8-5/8"	24-32#	3231'	12-1/4"	1350sx-Circ	N/A
5-1/2"	15.5-17#	10445'	7-7/8"	2250sx-Circ	N/A

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					---	---	---

26. Perforation record (interval, size, and number) 2SPF @ 7240-48,52-69,7274-7310,20-7336' Total 158 holes	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1"> <thead> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> </thead> <tbody> <tr> <td>10445-10528'</td> <td>1000g 15% HCl acid</td> </tr> <tr> <td>7240-7336'</td> <td>8000g 17% Fercheck SC acid</td> </tr> </tbody> </table>	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	10445-10528'	1000g 15% HCl acid	7240-7336'	8000g 17% Fercheck SC acid
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED						
10445-10528'	1000g 15% HCl acid						
7240-7336'	8000g 17% Fercheck SC acid						


28. PRODUCTION

Date First Production ---	Production Method (Flowing, gas lift, pumping - Size and type pump) ---	Well Status (Prod. or Shut-in) SI - W/O P&A					
Date of Test ---	Hours Tested ---	Choke Size ---	Prod'n For Test Period	Oil - Bbl. ---	Gas - MCF ---	Water - Bbl. ---	Gas - Oil Ratio ---
Flow Tubing Press. ---	Casing Pressure ---	Calculated 24-Hour Rate	Oil - Bbl. ---	Gas - MCF ---	Water - Bbl. ---	Oil Gravity - API (Corr.) ---	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
 --- Test Witnessed By

30. List Attachments
 C-103. Deviation Survey. Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature  Printed Name David Stewart Title Sr. Reg Analyst Date 6/15/03

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northeastern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2912'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 3172'	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3737'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____ 9816'	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____ 5541'	T. McKee _____ 10114'	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____ 10463'	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____ 10522'	T. Morrison _____	T. _____
T. Tubb _____ 6521'	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____ 7031'	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____

No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1500	1500	Red Beds	8450	8600	150	Lime, sand, chert
1500	2900	1400	Red Beds, Salt	8600	9060	460	Lime
2900	4100	1200	Anhyd. shale, dolomite	9060	9800	740	Chert, lime, dolom
4100	5300	1200	Dolomite	9800	10030	230	Chert, lime, shale
5300	5550	250	Limestone	10030	10464	434	Sndst, shale
5550	6530	980	Dolom, lime, anhyd	10464	10522	58	Dolom, lime
6530	7050	520	Dolomite	10522	10526	4	Granite
7050	7160	110	Limestone				
7160	7520	360	Dolomite				
7520	7590	70	Limestone				
7590	7700	110	Chert, lime, dolom				
7700	7750	50	Lime, dolom				
7750	7790	40	Shale, sand				
7790	8270	480	Limestone				
8270	8450	180	Dolomite				