Form 3160-5 (April 2004)

UNITED STATES OCD-HOBBS DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No 1004-0137 Expires: March 31, 2007

| - | , ortaine or arms in | | | J. Lease Schai No. | |
|--|--|--|--|---|----------------------------|
| SUNDRY | NOTICES AND REF | PORTS ON WI | ELLS | NM 98157 9883\ | |
| Do not use th | nis form for proposals t ell. Use Form 3160-3 (A | to drill or to re- | -enter an | 6. If Indian, Allottee or Tribe Name | |
| SUBMIT IN TRI | IPLICATE- Other instr | ructions on reve | erse side. | 7. If Unit or CA/Agreement, Name and/or N | 0 |
| I Type of Well | | | 8. Well Name and No. | | |
| 2 Name of Operator CHI Operating, Inc. | | | | Salado Fed. #1 9. API Well No. | |
| 3a Address | | 3b. Phone No. (include area code) 432-685-5001 | | 30-025-38402 | |
| P.O. Box 1799, Midland, Texas 79792 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | | 432-003-3001 | | 10. Field and Pool, or Exploratory Area Wildcat Delaware | |
| 2310' FSL & 1850' FWL | Sec. 8-T26S-R34E | | | 11. County or Parish, State | |
| | Unit K | | | Lea Co., New Mexico | |
| 12. CHECK AI | PPROPRIATE BOX(ES) TO |) INDICATE NATU | JRE OF NOTICE, 1 | REPORT, OR OTHER DATA | |
| TYPE OF SUBMISSION | | T | YPE OF ACTION | | |
| Notice of Intent | Acidize Alter Casing Casing Repair | Deepen Fracture Treat New Construction | Production (S Reclamation Recomplete | tart/Resume) | |
| Subsequent Report | Change Plans | Plug and Abandon | , | | |
| Final Abandonment Notice | Convert to Injection | Plug Back | Water Disposa | <u> </u> | |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Find determined that the site is ready | ectionally or recomplete horizontall the work will be performed or provi- volved operations. If the operation nal Abandonment Notices shall be y for final inspection.) | lly, give subsurface locat vide the Bond No. on file n results in a multiple con e filed only after all requi | ions and measured and to e with BLM/BIA. Requi npletion or recompletion rements, including reclar | rue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed or nation, have been completed, and the operator ha | nes. ys nce ss |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp | ectionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .125i | lly, give subsurface locat vide the Bond No. on file a results in a multiple con e filed only after all requi p 928'. Ran 8 5/8" J55 5#CF, Circ 113sx t/pit s. Log depth @ 5580', sxs "C"+add @3290' | ions and measured and to e with BLM/BIA. Requi appletion or recompletion frements, including reclar 5.24# surface csg. Cm e. WOC 21 hrs. NU, T TIH w/ 4 1/2" open by WOC, tg plug @ 31 | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP 100 sxs "C"+add@114 bt surf plug. WOC, spot 10 sxs "C" @ 60. | nes, ys nce s + all 3', ND |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drld a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 | ectionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1250" TD. Circ. for open hole logs. 1190', circ. hole spot CBP 100 spot 75 sxs CBP "C"+add @ 98 | lly, give subsurface locat vide the Bond No. on file n results in a multiple con e filed only after all requi p 928'. Ran 8 5/8" J55 #CF, Circ 113sx t/pit s. Log depth @ 5580'. sxs "C"+add @3290' 84', WOC, TIH tg plu | ions and measured and the with BLM/BIA. Requirements, including reclarity and the work of | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP 100 sxs "C"+add@114 bt surf plug. WOC, spot 10 sxs "C" @ 60. | nes, ys nce s + all 3', ND |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp | ectionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .125i | lly, give subsurface located the Bond No. on file in results in a multiple content of the filed only after all requisions of the well both setting of the well between the well | ions and measured and the with BLM/BIA. Requirements, including reclarity and the work of | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP'100 sxs "C"+add@114 bt surf plug. WOC, spot 10 sxs "C" @ 60', ACCEPTED FOR RECOR | nes, ys nce s + all 3', ND |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. | cetionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1256" TD. Circ. for open hole logs. 190°, circ. hole spot CBP 100 soot 75 sxs CBP "C"+add @ 98 Approved as to plugging Liability under bond is Surface restoration is 6 | lly, give subsurface located the Bond No. on file in results in a multiple content of the filed only after all requisions of the well both setting of the well between the well | ions and measured and the with BLM/BIA. Requirements, including reclarity and the work of | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP'100 sxs "C"+add@114 ot surf plug. WOC, spot 10 sxs "C" @ 60', ACCEPTED FOR RECOR AUG 6 2007 IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK | nes, ys nee s + + |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. 4. I hereby certify that the fore Name (Printed/Typed) | cetionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1256 "TD. Circ. for open hole logs. (190", circ. hole spot CBP 100 spot 75 sxs CBP "C"+add @ 98 Approved as to pluggin Liability under bond is Surface restoration is comparison. | lly, give subsurface locativide the Bond No. on file in results in a multiple cone filed only after all requisions of the Month of the filed only after all requisions. Log depth @ 5580', sxs "C"+add @3290' 84', WOC, TIH tg plusing of the well both is retained until completed. | ions and measured and the with BLM/BIA. Requippletion or recompletion rements, including reclarity and the work of 24# surface csg. Cmt. WOC 21 hrs. NU, Tmt. TIH w/ 4 1/2" open young and | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP'100 sxs "C"+add@114 ot surf plug. WOC, spot 10 sxs "C" @ 60', ACCEPTED FOR RECOR AUG 6 2007 IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK | nes, ys nee s + + |
| If the proposal is to deepen dire Attach the Bond under which the Bond under which the following completion of the investing has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. | cetionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1256 "TD. Circ. for open hole logs. (190", circ. hole spot CBP 100 spot 75 sxs CBP "C"+add @ 98 Approved as to pluggin Liability under bond is Surface restoration is comparison. | lly, give subsurface locativide the Bond No. on file in results in a multiple cone filed only after all requisions of the Month of the filed only after all requisions. Log depth @ 5580', sxs "C"+add @3290' 84', WOC, TIH tg plusing of the well both is retained until completed. | ions and measured and the with BLM/BIA. Requirements, including reclarity and the work of | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP'100 sxs "C"+add@114 ot surf plug. WOC, spot 10 sxs "C" @ 60', ACCEPTED FOR RECOR AUG 6 2007 IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK IES BABYAK | nes, ys nee s + + |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. 4. I hereby certify that the fore Name (Printed/Typed) PAM CORBET | cetionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1256 "TD. Circ. for open hole logs. (190", circ. hole spot CBP 100 spot 75 sxs CBP "C"+add @ 98 Approved as to pluggin Liability under bond is Surface restoration is comparison. | lly, give subsurface located the Bond No. on file in results in a multiple content of the Bond No. on file in results in a multiple content of the Bond No. on file in results in a multiple content of the Bond No. on file in a multiple content of the Bond No. on file in a multiple content of the Well bond in a multiple in the Bond No. on file in a multiple content of the Bond No | ions and measured and the with BLM/BIA. Required pletion or recompletion rements, including reclarity to the surface csg. Cm. WOC 21 hrs. NU, Tm. TIH w/4 1/2" open the wood, the wood, the wood, the wood and the surface csg. Cm. WOC, tg plug @ 31 gg @ 804', TOH to specific. Regulatory Clerk | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had with with the depth of the within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had with with the operator had with with the series of the within the | nes, ys nee s + + |
| Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM, Tail Drld a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. 14. I hereby certify that the fore Name (Printed/Typed) PAM CORBETT Signature | cetionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .1256 "TD. Circ. for open hole logs. (190°, circ. hole spot CBP 100 so to 75 sxs CBP "C"+add @ 98 Approved as to pluggin Liability under bond is Surface restoration is compared to the compared t | lly, give subsurface located the Bond No. on file in results in a multiple content of the Bond No. on file in results in a multiple content of the Bond No. on file in results in a multiple content of the Bond No. on file in a multiple content of the Bond No. on file in a multiple content of the Well bond in a multiple in the Bond No. on file in a multiple content of the Bond No | ions and measured and the with BLM/BIA. Requippletion or recompletion rements, including reclaims 24# surface csg. Cmt. WOC 21 hrs. NU, Tmt. TIH w/ 4 1/2" open, WOC, tg plug @ 31 g @ 804', TOH to specific. Regulatory Clerk | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs.cmt b 13', circ., spot CBP 100 sxs "C" + add@114 ot surf plug. WOC, spot 10 sxs "C" @ 60'. ACCEPTED FOR RECOR AUG 6 2007 LES BABYAK PETROLEUM ENGINEER PETROLEUM ENGINEER | nes, ys nee s + + |
| If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Find determined that the site is ready 5/29/07 Spud well(notified 2% CACL + 3#LCM. Tail Drid a 7 7/8" hole to 5580 plug @ 5560', tg plug @ 5 WOC, TIH tg @ 1020', sp BOP, RD and release rig. 14. I hereby certify that the fore Name (Printed/Typed) PAM CORBET | ectionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) I BLM). Drld a 12 3/4" hole to 1150sx "C" 2% CACL + .125; TD. Circ. for open hole logs. 190', circ. hole spot CBP 100 s foot 75 sxs CBP "C"+add @ 98. Approved as to plugging Liability under bond is Surface restoration is considered. THIS SPACE FOR | lly, give subsurface locativide the Bond No. on file in results in a multiple cone filed only after all requipe 928'. Ran 8 5/8" J55 5#CF, Circ 113sx t/pit s. Log depth @ 5580'. sxs "C"+add @3290' 34', WOC, TIH tg plusing of the well both is retained until completed. Title Date FEDERAL OR | ions and measured and the with BLM/BIA. Required pletion or recompletion rements, including reclarity to the surface csg. Cm. WOC 21 hrs. NU, Tm. TIH w/4 1/2" open the wood, the wood, the wood, the wood and the surface csg. Cm. WOC, tg plug @ 31 gg @ 804', TOH to specific. Regulatory Clerk | nue vertical depths of all pertinent markers and zo red subsequent reports shall be filed within 30 da in a new interval, a Form 3160-4 shall be filed on nation, have been completed, and the operator had w/Lead 35:65 POZ "C" 305sx 6% GEL st BOP, Tst csg t/2000#-all ok. end DP tg up @ 5580'. Spot 100 sxs cmt b 13', circ., spot CBP:100 sxs "C"+add@114 ot surf plug. WOC, spot 10 sxs "C" @ 60', ACCEPTED FOR RECOR AUG 6 2007 IES BABYAK PETROLEUM ENGINEER | nes, ys nee s + + |