

Office

June 19, 2008

District I

1625 N French Dr., Hobbs, NM 88241

District II

1301 W Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87411

District IV

1220 S St Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-03884

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

WEST LOVINGTON UNIT

8. Well Number 20

9. OGRID Number 241333

10. Pool name or Wildcat

LOVINGTON UPPER SAN ANDRES W.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other INJECTION ☒

2. Name of Operator

CHEVRON MIDCONTINENT, L.P.

3. Address of Operator

15 SMITH ROAD, MIDLAND, TEXAS 79705

4. Well Location

Unit Letter J: 1980 feet from the SOUTH line and 1980 feet from the EAST line

Section 5 Township 17-S Range 36-E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: REPAIR SURFACE CSG

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

CHEVRON MIDCONTINENT, L.P. INTENDS TO REPAIR THE SURFACE CASING IN THE SUBJECT WELL. VERBAL APPROVAL RECEIVED FROM MAXEY BROWN 08-08-08.

1) RBP'S ARE ALREADY SET FROM SURFACE @ 4030 & 685 W/15.4 MUD BETWEEN BOTH RBP'S & 10# BRINE W/PKR FLUID ABOVE RBP SET @ 685 FROM SURF. 2) PREP 13.375 SURFACE CSG TO CUT WINDOWS ON 13.375 SURFACE CSG. CUT WINDOWS 8 5/8" & CUT & RELAX THE 5.5 PROD CSG. 3) PULL OUT WITH ALL CUT OFF CSGS, 13.375, 8 5/8, & 5.5 4) DRESS CSGS TO START BUILDING BACK. 5) PLATE & WELD COLLAR FOR MONITORING ON 13 3/8" 6) PLATE & WELD COLLAR FOR MONITORING ON 8 5/8". 7) SLIP COLLAR 5.5, WELD 5.5 CSG TO SURF. 8) BUILD & INSTALL RISERS. 9) INSTALL TBG HEAD W/BELL NIPPLE. 10) CALL NMOC TO WITNESS BEFORE BACK FILLING HOLE.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Denise Pinkerton

TITLE REGULATORY SPECIALIST

DATE 08-19-2008

Type or print name

DENISE PINKERTON

E-mail address: leakejd@chevron.com

PHONE: 432-687-7375

For State Use Only

APPROVED BY:

Chris Williams

OC DISTRICT SUPERVISOR/GENERAL MANAGER

TITLE

DATE

AUG 25 2008

Conditions of Approval (if any):