

New Mexico Oil Conservation Division, District I
1625 N. French Drive
Hobbs, NM 88240

Form 3160-5
(September 2001)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No 1004-0135
Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS

*Do not use this form for proposals to drill or re enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.*

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well



Oil Well



Gas Well



Other



2 Name of Operator

Yates Drilling Company

3a Address

105 S. 4th Str., Artesia, NM 88210

3b Phone No (include area code)

505-748-8663

4 Location of Well (Footage, Sec., T., R., M., OR Survey Description)

1650' FNL & 660' FEL Section 34-12S-31E

Unit-H

5. Lease Serial No.

NMNM90584

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8 Well Name and No

Garner Federal #10

9. API Well No

30-005-21139

10. Field and Pool, or Exploratory Area

SE Chaves QN Gas Area Assoc

11 County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☒ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☐ Other

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

See Attachment.

RECEIVED

AUG 17 2009

HOBBSOCD

Approved as to plugging of the
well bore. Liability under bond
is retained until surface resto-
ration is completed.

14 I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Karen J. Leishman

Title

Operations Tech

Signature

Karen J. Leishman

Date

6/5/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

/S/ **DAVID R. GLASS**

Title

PETROLEUM ENGINEER

Date

JUN 16 2009

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

ROSSELL FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Yates Drilling Company
Garner Federal #10
Unit N, Section 34-12S-31E
Chaves County, NM
30-005-21139
Sundry attachment
June 5, 2009

5/8/2009 RU Plugging Unit. POH with rods.
5/11/2009 POH with 2 7/8" tubing. Set CIBP at 2,950'. Circulated hole with 50 bbls
 10# mud. Spotted 25 sxs cement on top of CIBP. Spotted 25 sxs cement
 at 2,150', base of salt.
5/12/2009 Tagged plug at 1,904'. Spotted 25 sxs cement from 1,450' to 1,203'. RIH
 and perforated at 650'. Set packer and pumped 10# mud circulating thru
 5 1/2" casing out 8 5/8" casinghead. Pumped 160 sxs cement, circulating
 cement out 8 5/8" casinghead to surface out 5 1/2" casing. Cleaned
 location and installed dry hole marker.

NOTE: Eddie Fitzpatrick, BLM witnessed plugging.