Form 3160-5 **UNITED STATES** FORM APPROVED RECEIVED (November 1994) DEPARTMENT OF THE INTERIOR OMB No. 1004-0135 **BUREAU OF LAND MANAGEMENT** Expires July 31, 1996 Lease Serial No. OTHER FEB 4500 SUNDRY NOTICES AND REPORTS ON WELLS

AND REPORTS OF WELLS form for proposals to drill or to re-enter an LC-063586 If Indian, Allottee or Tribe Name abandoned well. Use form 3160-3 (APD) for such proposals. If Unit or CA/Agreement, Name and/or No SUBMIT IN TRIPLICATE - Other instructions on reverse side Type of Well X Oil Well Gas Well Other Well Name and No. Southern California 29 Federal No. 15 Name of Operator Cimarex Energy Co. of Colorado 9. API Well No. Phone No. (include area code) 30-025-39634 600 N. Marienfeld St., Ste. 600; Midland, TX 79701 432-571-7800 Field and Pool, or Exploratory Area Location of Well (Footage, Sec., T., R, M., or Survey Description) Lusk; Bone Spring, S SHL 375 FSL & 330 FWL 29-19S-32E 11. County or Parish, State BHL 330 FSL & 330 FEL Lea, NM CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Acidize Deepen Production (Start/Resume) Water Shut-Off Alter Casing Fracture Treat Well Integrity Reclamation Other Change casing, New Construction Subsequent Report Casing Repair Recomplete due to H2S kick at 8132' Change Plans Plug and Abandon Temporanly Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, included estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Change 7" casing setting depth and grade from 8700' 26# P-110 LTC to 0'-7550' 26# P-110 LTC and 7550'-8550' 29# L-80 LTC due to a drilling break with H2S at 8132'-8148'. Cementing plan remains same as permitted (TOC minimum tie-in 200' into intermediate casing). Fiberglass tubing will be eliminated, but we will drill out of the 7" casing to original pilot hole TD of 9550' and log. After logging, we will cement hole to original KOP of 8759' to drill the lateral. Lateral casing and cement will remain the same. Liner top will be 8450' (propose 100' tieback in order to set pump as deep as possible once completed). SEE ATTACHED FOR CONDITIONS OF APPROVAL 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Zeno Farris Manager Operations Administration Signature

Zeno Farris

Signature

Date

February 16, 2010

APPROVED

Approved by

Conditions of Approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Manager Operations Administration

Date

February 16, 2010

Title

Office

Office

/S/ Chris Walls

BUREALL OF LAND MANAGEMENT

Title 18 U.S C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false inclinious of LD OFFICE fraudulent statements or representations as to any matter within its jurisdiction.

## Southern California 29 Fed #15 30-025-39634 Cimarex Energy Co. of Colorado February 22, 2010 Conditions of Approval

1. Pilot hole is required to have a plug at the bottom of the hole. If two plugs are set, the BLM is to be contacted (575-393-3612) prior to tag of bottom plug, which must be a minimum of 200' in length. Operator can set one plug from bottom of pilot hole to kick-off point and save the WOC time for tagging the first plug.

**CRW 022210**