

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

May 27, 2004

RECEIVED

## OIL CONSERVATION DIVISION

MAR 25 2010

HOBBSOCD

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30 - 025 - 32251

13. Indicate Type of Lease

STATE ☒ FEE ☐

13. State Oil &amp; Gas Lease No.

B-2139-3

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☒

2. Name of Operator

BP America Production Company

3. Address of Operator

P. O. Box 1089 Eunice, New Mexico 88231

7. Lease Name or Unit Agreement Name

State "H"

8. Well Number

6

9. OGRID Number

000778

10. Pool name or Wildcat

Eumont Yates 7RQ

13. Well Location

Unit Letter P : 3300 feet from the South line and 990 feet from the East line  
Section 5 Township 21S Range 36E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3585' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

## 13. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

MIRU PU and ancillary P&A equipment on 3/8/10. Killed well, installed BOP, worked tubing free and POH & LD production tubing. Made trip w/ 4 3/4" bit & 5 1/2" scraper on 2 3/8" workstring to top of fill @ 3305', OK. TIH w/ 5 1/2" CIBP on tubing and set @ 2664' = 55' above top perf in Yates - tested CIBP & 5 1/2" casing to 500 psi, OK. Circulated hole with 9.5 ppg mud laden fluid and spotted 25 sx Class "C" onto CIBP, top of cement @ approx 2365'; this sets bottom plug and places plug across B/Salt @ 2550'. POH & LD tubing to 1300' and spotted 30 sx Class "C" to approx 1005', which placed plug across the T/Salt @ 1200'. POH & LD tubing to 450' = 50' below the 8 5/8" surface casing shoe @ 400'. Mixed & pumped 45 Class "C" and had good cement slurry returned to surface. POH & LD all tubing - left 5 1/2" csg filled with cement from 0' - 450'. RD & MO PU, downhole plugging operations completed on 3/12/10. Cut-off WH & anchors to 3' below GL and installed regulation Dry Hole Marker on 3/19/10. NMOCD will be notified when site has been reclaimed and ready for final inspection.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, www.cmnrd.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Steve M. Pacheco TITLE Area Operations Team Lead - SENM DATE 3/23/10Type or print name Steve M. Pacheco E-mail address: steve.pacheco@bp.com Telephone No. 575/394-1648

## For State Use Only

APPROVED BY: [Signature] TITLE Staff MGR DATE 3-25-10

Conditions of Approval (if any):

**State "H" #6**  
 Eumont Yates Field  
  
 API No. 30-025-32251  
 State Lease No. B-2139-3  
  
 3300' FSL & 990' FEL  
 Sec 5 - T21S - R36E  
 Lea County, New Mexico

**Final P&A Status**  
 March 19, 2010

RKB 12'  
 GL 3585'

"H"  
 #6

**Surface Plug**  
 0' - 450'  
 45 sx Class "C"  
 Plug set 3/12/10

Spud 10/16/93  
 Comp 11/29/93  
 P&A 3/12/10  
 Life of Well 5991 days

8 5/8" 24# J55 @ 400'  
 Cmt'd w/ 350 sx, circ to surface

**T/Salt Plug**  
 1005' - 1300'  
 30 sx Class "C"  
 Plug set 3/11/10

T/Salt @ 1200'

**Yates - B/Salt Plug**  
 2365' - 2664'  
 Set CIBP @ 2664' &  
 capped w/ 30 sx  
 Class "C" to 2365'  
 Plug set 3/11/10

B/Salt @ 2550'

Yates @ 2714'

Perfs  
 2719 2732 2741 2758 2796 2823  
 2874 2902 2935 2953 3016 3105  
 3164 3165 3245 3266 3376 3396  
 3413 3417 3433 3436 3445 3450  
 3454 3471 3490 3510 3526 3527  
 3540 3550 3557 3596 3602

1 SPF = 35 - 0.40" holes

Tag fill @ 3305'

3650' PBD  
 3700' TD

5 1/2" 15.5# J-55 LTC @ 3700'  
 Cmt'd w/ 850 sx to surface