

RECEIVED

MAR 31 2010

HOBBSD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-39636

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

NA

7. Lease Name or Unit Agreement Name

Arnold A

8. Well Number 3

9. OGRID Number

873

10. Pool name or Wildcat

House; Blinebry/Tubb/Drinkard

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other:

2. Name of Operator

Apache Corporation

3. Address of Operator

6120 S Yale Ave, Suite 1500 Tulsa, OK 74136

4. Well Location

Unit Letter F : 1650 feet from the North line and 2310 feet from the West line

Section 11 Township 20S Range 38E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3588'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: New Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Apache completed this well via the following procedure:

3/2/10 Perf Drinkard @ 6983-6987, 7020-7028, 7066-7070, 7094-7098 w/2 JSPF. 44 holes.

3/3/10 Acidized w/2k gals 15% HCl.

3/4/10 Frac w/57435 gals gel & 80431# 20/40 sd. Set CBP @ 6855'. Perf Tubb @ 6674-6678, 6742-6746, 6756-6760, 6778-6788 w/2 JSPF. 48 holes. Acidized Tubb w/2058 gals 15% HCl.

3/5/10 Frac w/34978 gals gel & 78398# 20/40 sd. Set CBP @ 6400'. Perf Blinebry @ 6060-6070, 6128-6138, 6152-6156, 6206-6210, 6318-6322, 6354-6358 w/2 JSPF. 78 holes. Acidized w/5158 gals 15% HCL. Frac w/39287 gals gel & 84981# 20/40 sd. 3/8/10 DO CBP's.

3/9/10 Wash sand to PBTD @ 7203'.

3/10/10 RIH w/prod equip. Tbg @ 7095'. Set 640 pumping unit.

3/12/10 Send prod to battery. Producing Blinebry/Tubb/Drinkard.

DHC-HDB-0359

Spud Date: 02/09/2010

Rig Release Date: 02/16/2010

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Amber Cooke TITLE Engineering Tech

DATE 03/30/2010

Type or print name Amber Cooke

E-mail address: amber.cooke@apachecorp.com

PHONE: 918.491.4968

For State Use Only

APPROVED BY: [Signature]

TITLE PETROLEUM ENGINEER

DATE

APR 08 2010

Conditions of Approval (if any):