


OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO



DUPLICATE

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

May 29, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation State of NM "D" Well No. 3 in the Company or Operator Lease C/SE/4 SE/4 of Sec. 35, T. 11-S, R. 33-E, N. M. P. M., Bagley-Siluro/Devonian Field Lea County.

The dates of this work were as follows: May 28, 1950

Notice of intention to do the work was submitted on Form C-102 on May 28, 1950

and approval of the proposed plan was obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3866' - Total Depth - Lime. Run Schlumberger Electrical & Gamma Ray Surveys. Run 101 Joints of 8-5/8" O.D. 32#, 8-Md. Td., Grade J-55, Range 3, S. S. New casing, set at 3866' and cemented with 1000 sacks Atlas Regular cement mixed 1/3% Jell, 450 sacks Lone Star Regular Cement & 50 Sacks Inocer Cement - Total of 1500 sacks. Plug to 3744' at 5:45 P.M., 5-29-50. Maximum pump pressure 1200#.

Witnessed by E. V. Stephenson Amerada Petroleum Corporation Foreman Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

29th day of May, 1950

Name Du Topp

Position Assistant District Superintendent

Notary Public

Representing Amerada Petroleum Corporation Company or Operator

My commission expires 10-24-53

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED JUN 1 1950 Date

Oil & Gas Inspector Name Title